

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2024
6.0	04/14/2025	656848-00022	Date of first issue: 05/02/2016

SECTION 1. IDENTIFICATION

Product name : Bismuth Subnitrate Formulation

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc
Address : 126 E. Lincoln Avenue
Rahway, New Jersey U.S.A. 07065
Telephone : 908-740-4000
Emergency telephone : 1-908-423-6000
E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization : Category 1
Specific target organ toxicity : Category 1 (Central nervous system)
- repeated exposure

Other hazards

None known.

GHS label elements

Hazard pictograms :

Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P261 Avoid breathing dust, fume, gas, mist, vapors or spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of water.
P314 Get medical attention if you feel unwell.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation

Version 6.0 Revision Date: 04/14/2025 SDS Number: 656848-00022 Date of last issue: 09/28/2024
Date of first issue: 05/02/2016

P333 + P313 If skin irritation or rash occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Bismuth hydroxide nitrate oxide	1304-85-4*	$\geq 45 - \leq 70$	TSC
Petrolatum	8009-03-8*	$\geq 10 - \leq 30$	TSC
Zinc oxide	1314-13-2*	$\geq 3 - \leq 7$	TSC
Benzyl alcohol	100-51-6*	$\geq 0.5 - \leq 1.5$	TSC

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
Causes damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2024
6.0	04/14/2025	656848-00022	Date of first issue: 05/02/2016

Notes to physician : when the potential for exposure exists (see section 8).
: Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Nitrogen oxides (NO_x)
Metal oxides
Carbon oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation

Version 6.0 Revision Date: 04/14/2025 SDS Number: 656848-00022 Date of last issue: 09/28/2024
Date of first issue: 05/02/2016

determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Avoid breathing dust, fume, gas, mist, vapors or spray.
Do not swallow.
Avoid contact with eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Explosives
Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Petrolatum	8009-03-8	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Zinc oxide	1314-13-2	TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
		STEL (Respirable particulate matter)	10 mg/m ³	ACGIH
		TWA (Dust)	5 mg/m ³	NIOSH REL
		TWA	5 mg/m ³	NIOSH REL

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation

Version 6.0 Revision Date: 04/14/2025 SDS Number: 656848-00022 Date of last issue: 09/28/2024
Date of first issue: 05/02/2016

		(Fumes)		
		ST (Fumes)	10 mg/m ³	NIOSH REL
		C (Dust)	15 mg/m ³	NIOSH REL
		TWA (Fumes)	5 mg/m ³	OSHA Z-1
		TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
Benzyl alcohol	100-51-6	TWA	10 ppm	US WEEL

Engineering measures : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2024
6.0	04/14/2025	656848-00022	Date of first issue: 05/02/2016

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	paste
Color	:	white
Odor	:	Petroleum
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not classified as a flammability hazard
Flammability (liquids)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	No data available
Solubility(ies)		
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2024
6.0	04/14/2025	656848-00022	Date of first issue: 05/02/2016

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics
Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : Can react with strong oxidizing agents.
Conditions to avoid : None known.
Incompatible materials : Oxidizing agents
Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

Bismuth hydroxide nitrate oxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 423
Remarks: Based on data from similar materials
Acute inhalation toxicity : LC50 (Rat): > 5.07 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 436
Remarks: Based on data from similar materials

Petrolatum:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials
Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation

Version 6.0 Revision Date: 04/14/2025 SDS Number: 656848-00022 Date of last issue: 09/28/2024
Date of first issue: 05/02/2016

toxicity

Remarks: Based on data from similar materials

Zinc oxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 5.7 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Benzyl alcohol:

Acute oral toxicity : LD50 (Rat): 1,200 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 5.4 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439

Result : No skin irritation

Petrolatum:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Zinc oxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Benzyl alcohol:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2024
6.0	04/14/2025	656848-00022	Date of first issue: 05/02/2016

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

Petrolatum:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
Remarks	:	Based on data from similar materials

Zinc oxide:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

Benzyl alcohol:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days
Method	:	OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	negative

Petrolatum:

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2024
6.0	04/14/2025	656848-00022	Date of first issue: 05/02/2016

Result	: negative
Remarks	: Based on data from similar materials

Zinc oxide:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

Benzyl alcohol:

Test Type	: Human repeat insult patch test (HRIPT)
Routes of exposure	: Skin contact
Species	: Humans
Result	: positive

Assessment	: Probability or evidence of low to moderate skin sensitization rate in humans
------------	--

Germ cell mutagenicity

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative Remarks: Based on data from similar materials
	Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
	Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative

Petrolatum:

Genotoxicity in vitro	: Test Type: Chromosome aberration test in vitro Result: negative Remarks: Based on data from similar materials
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: negative Remarks: Based on data from similar materials

Zinc oxide:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2024
6.0	04/14/2025	656848-00022	Date of first issue: 05/02/2016

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: equivocal Test Type: Chromosome aberration test in vitro Result: equivocal
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: inhalation (dust/mist/fume) Method: OECD Test Guideline 474 Result: negative Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Rat Application Route: inhalation (dust/mist/fume) Result: positive Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: negative
Germ cell mutagenicity - Assessment	: Weight of evidence does not support classification as a germ cell mutagen.

Benzyl alcohol:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Petrolatum:

Species	: Rat
Application Route	: Ingestion
Exposure time	: 2 Years
Result	: negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2024
6.0	04/14/2025	656848-00022	Date of first issue: 05/02/2016

Zinc oxide:

Species	: Mouse
Application Route	: Ingestion
Exposure time	: 1 Years
Result	: negative
Remarks	: Based on data from similar materials

Benzyl alcohol:

Species	: Mouse
Application Route	: Ingestion
Exposure time	: 103 weeks
Method	: OECD Test Guideline 451
Result	: negative

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Effects on fertility	: Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: Ingestion Result: negative
Effects on fetal development	: Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Method: OECD Test Guideline 414 Result: negative

Petrolatum:

Effects on fertility	: Test Type: Reproduction/Developmental toxicity screening test Species: Rat Application Route: Ingestion Result: negative Remarks: Based on data from similar materials
Effects on fetal development	: Test Type: Embryo-fetal development

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2024
6.0	04/14/2025	656848-00022	Date of first issue: 05/02/2016

Species: Rat
Application Route: Skin contact
Result: negative
Remarks: Based on data from similar materials

Zinc oxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (dust/mist/fume)
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Benzyl alcohol:

Effects on fertility : Test Type: Fertility/early embryonic development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Application Route: Ingestion
Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Components:

Bismuth hydroxide nitrate oxide:

Target Organs : Central nervous system
Assessment : Causes damage to organs through prolonged or repeated exposure.

Zinc oxide:

Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2024
6.0	04/14/2025	656848-00022	Date of first issue: 05/02/2016

Repeated dose toxicity

Components:

Petrolatum:

Species	: Rat
NOAEL	: 5,000 mg/kg
Application Route	: Ingestion
Exposure time	: 2 y

Zinc oxide:

Species	: Rat, male
NOAEL	: 0.0015 mg/l
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 3 Months
Method	: OECD Test Guideline 413

Benzyl alcohol:

Species	: Rat
NOAEL	: 1.072 mg/l
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 28 Days
Method	: OECD Test Guideline 412

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Product:

Ingestion	: Symptoms: The absorption of this product into the body may lead to the formation of methaemoglobine that, in sufficient concentration, causes cyanosis., May cause, Neurological disorders, Blood disorders, blood effects, central nervous system effects, Methaemoglobinemia
-----------	--

Components:

Bismuth hydroxide nitrate oxide:

Ingestion	: Target Organs: Blood Symptoms: Methaemoglobinemia Target Organs: Central nervous system Symptoms: Neurological disorders
-----------	---

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Bismuth hydroxide nitrate oxide:

Toxicity to fish	: LL50 (Danio rerio (zebra fish)): > 137 mg/l
------------------	---

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2024
6.0	04/14/2025	656848-00022	Date of first issue: 05/02/2016

	Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 137 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: EL50 (Pseudokirchneriella subcapitata (green algae)): > 137 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201
	NOELR (Pseudokirchneriella subcapitata (green algae)): > 137 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201

Petrolatum:

Toxicity to fish	: LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	: NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 10 mg/l Exposure time: 21 d Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Zinc oxide:

Toxicity to fish	: LC50 : > 0.1 - 1 mg/l Exposure time: 96 h Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	: ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.136 mg/l

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2024
6.0	04/14/2025	656848-00022	Date of first issue: 05/02/2016

	Exposure time: 72 h
	NOEC (Pseudokirchneriella subcapitata (green algae)): > 0.01 - 0.1 mg/l
	Exposure time: 72 h
	Remarks: Based on data from similar materials
Toxicity to fish (Chronic toxicity)	: NOEC (Jordanella floridae (flagfish)): > 0.01 - 0.1 mg/l
	Exposure time: 14 Weeks
	Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Ceriodaphnia dubia (water flea)): > 0.01 - 0.1 mg/l
	Exposure time: 7 d
	Remarks: Based on data from similar materials

Benzyl alcohol:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 460 mg/l
	Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 230 mg/l
	Exposure time: 48 h
	Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: EC50 (Pseudokirchneriella subcapitata (green algae)): 770 mg/l
	Exposure time: 72 h
	Method: OECD Test Guideline 201
	NOEC (Pseudokirchneriella subcapitata (green algae)): 310 mg/l
	Exposure time: 72 h
	Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 51 mg/l
	Exposure time: 21 d
	Method: OECD Test Guideline 211

Persistence and degradability

Components:

Petrolatum:

Biodegradability	: Result: Not readily biodegradable.
	Biodegradation: 31 %
	Exposure time: 28 d
	Method: OECD Test Guideline 301F
	Remarks: Based on data from similar materials

Benzyl alcohol:

Biodegradability	: Result: Readily biodegradable.
	Biodegradation: 92 - 96 %
	Exposure time: 14 d

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2024
6.0	04/14/2025	656848-00022	Date of first issue: 05/02/2016

II

Bioaccumulative potential

Components:

Zinc oxide:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 78 - 2,060

Benzyl alcohol:

Partition coefficient: n-octanol/water : log Pow: 1.05

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.
Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)
Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 956
Packing instruction (passenger aircraft) : 956

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2024
6.0	04/14/2025	656848-00022	Date of first issue: 05/02/2016

Environmentally hazardous : yes

IMDG-Code

UN number	: UN 3077
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc oxide, 2,6-Di-tert-butyl-p-cresol)
Class	: 9
Packing group	: III
Labels	: 9
EmS Code	: F-A, S-F
Marine pollutant	: yes

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number	: UN 3077
Proper shipping name	: Environmentally hazardous substance, solid, n.o.s. (Zinc oxide, 2,6-Di-tert-butyl-p-cresol)
Class	: 9
Packing group	: III
Labels	: CLASS 9
ERG Code	: 171
Marine pollutant	: yes(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)
Remarks	: Above applies only to containers over 119 gallons or 450 liters. Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	: Respiratory or skin sensitization Specific target organ toxicity (single or repeated exposure)
----------------------	---

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2024
6.0	04/14/2025	656848-00022	Date of first issue: 05/02/2016

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Zinc oxide	1314-13-2	>= 5 - < 10 %
------------	-----------	---------------

US State Regulations

Pennsylvania Right To Know

Bismuth hydroxide nitrate oxide	1304-85-4
Petrolatum	8009-03-8
Zinc oxide	1314-13-2
Oleic acid	112-80-1
Benzyl alcohol	100-51-6

California List of Hazardous Substances

Petrolatum	8009-03-8
Zinc oxide	1314-13-2

California Permissible Exposure Limits for Chemical Contaminants

Petrolatum	8009-03-8
Zinc oxide	1314-13-2

The ingredients of this product are reported in the following inventories:

AICS	: not determined
DSL	: not determined
IECSC	: not determined

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation


Version
6.0

Revision Date:
04/14/2025

SDS Number:
656848-00022

Date of last issue: 09/28/2024
Date of first issue: 05/02/2016

NFPA 704:



HMIS® IV:

HEALTH	*	3
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
US WEEL	:	USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	:	8-hour time weighted average
US WEEL / TWA	:	8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Pre-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2024
6.0	04/14/2025	656848-00022	Date of first issue: 05/02/2016

vention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 04/14/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8