according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 4019096-00019 Date of first issue: 02/25/2019

SECTION 1. IDENTIFICATION

Product name : Flumethrin (1%) Formulation

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc Address : 126 E. Lincoln Avenue

Rahway, New Jersey U.S.A. 07065

Telephone : 908-740-4000 Emergency telephone : 1-908-423-6000

E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3

Acute toxicity (Oral) : Category 4

Acute toxicity (Dermal) : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Reproductive toxicity : Category 1B

Specific target organ toxicity

- single exposure (Oral)

Jity

Specific target organ toxicity :

Category 1

Category 1

- repeated exposure (Oral)

Specific target organ toxicity:

Category 2 (Auditory system)

- repeated exposure

Aspiration hazard : Category 1

Other hazards

Vapors may form explosive mixture with air.

GHS label elements

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 4019096-00019 Date of first issue: 02/25/2019

Hazard pictograms









Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin. H315 Causes skin irritation.

H319 Causes serious eye irritation. H360D May damage the unborn child.

H370 Causes damage to organs if swallowed.

H372 Causes damage to organs through prolonged or repeated

exposure if swallowed.

H373 May cause damage to organs (Auditory system) through

prolonged or repeated exposure.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P210 Keep away from heat, sparks, open flame and hot surfac-

es. No smoking.

P233 Keep container tightly closed.

P241 Use explosion-proof electrical, ventilating and lighting

equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P260 Do not breathe mist or vapors.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves, protective clothing, eye protection

and face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER.

P302 + P352 + P312 IF ON SKIN: Wash with plenty of soap and

water. Call a doctor if you feel unwell.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately

all contaminated clothing. Rinse skin with water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical attention.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical attention. P337 + P313 If eye irritation persists: Get medical attention.

Storage:

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 06/17/2025 4019096-00019 Date of first issue: 02/25/2019 6.0

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Paraffin oil	8012-95-1*	>= 60 - <= 80	TSC
Xylene	1330-20-7*	>= 7 - <= 13	TSC
Flumethrin	69770-45-2*	>= 0.5 - <= 1.5	TSC
Toluene	108-88-3*	>= 0.1 - <= 1	TSC

Indicates that the identifier is a CAS No.

SECTION 4. FIRST AID MEASURES

General advice In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled, remove to fresh air. If inhaled

Get medical attention.

In case of contact, immediately flush skin with plenty of water In case of skin contact

for at least 15 minutes while removing contaminated clothing

and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of contact, immediately flush eyes with plenty of water In case of eye contact

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed If swallowed, DO NOT induce vomiting.

If vomiting occurs have person lean forward.

Call a physician or poison control center immediately.

Rinse mouth thoroughly with water.

Never give anything by mouth to an unconscious person.

Most important symptoms

Harmful if swallowed.

and effects, both acute and

May be fatal if swallowed and enters airways. Toxic in contact with skin.

delayed

TSC- the actual concentration or concentration range is withheld as a trade secret

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 4019096-00019 Date of first issue: 02/25/2019

Causes skin irritation.

Causes serious eye irritation. May damage the unborn child.

Causes damage to organs if swallowed.

Causes damage to organs through prolonged or repeated

exposure if swallowed.

May cause damage to organs through prolonged or repeated

exposure.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not use a solid water stream as it may scatter and spread

fire.

Flash back possible over considerable distance. Vapors may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

icts

Carbon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Remove all sources of ignition.

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 4019096-00019 Date of first issue: 02/25/2019

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Non-sparking tools should be used. Soak up with inert absorbent material.

Suppress (knock down) gases/vapors/mists with a water spray

jet.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Use explosion-proof electrical, ventilating and lighting equip-

ment.

Advice on safe handling : Do not get on skin or clothing.

Do not breathe mist or vapors.

Do not swallow. Do not get in eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Non-sparking tools should be used. Keep container tightly closed.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store locked up. Keep tightly closed.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 4019096-00019 Date of first issue: 02/25/2019

Strong oxidizing agents

Self-reactive substances and mixtures

Organic peroxides Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures which in contact with water emit

flammable gases

Explosives Gases

Very acutely toxic substances and mixtures

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type		
		(Form of	ters / Permissible	
		exposure)	concentration	
Paraffin oil	8012-95-1	TWA (Mist)	5 mg/m³	OSHA Z-1
		TWA (Inhal- 5 mg/m ³		ACGIH
		able particu-		
		late matter)		
		TWA (Mist)	5 mg/m³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Xylene	1330-20-7	TWA	TWA 100 ppm O	
			435 mg/m ³	
		TWA	20 ppm	ACGIH
Flumethrin	69770-45-2	TWA	30 μg/m3 (OEB 3)	Internal
	Further information: Skin			
		Wipe limit		
Toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm	NIOSH REL
			375 mg/m³	
		ST	150 ppm	NIOSH REL
			560 mg/m ³	
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm	OSHA Z-2
			(10 minutes)	

Biological occupational exposure limits

Components	CAS-No.	Control	Biological	Sam-	Permissible	Basis
		parameters	specimen	pling	concentra-	
				time	tion	
Xylene	1330-20-7	Methylhippu ric acids	Urine	End of shift (As soon as possible after	0.3 g/g creatinine	ACGIH BEI

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 4019096-00019 Date of first issue: 02/25/2019

Toluene	108-88-3	Toluene	In blood	exposure ceases) Prior to last shift of work- week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g creatinine	ACGIH BEI

Engineering measures

Use appropriate engineering controls and manufacturing technologies to control airborne concentrations (e.g., dripless quick connections).

All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment.

Containment technologies suitable for controlling compounds

are required to control at source and to prevent migration of the compound to uncontrolled areas (e.g., open-face

containment devices). Minimize open handling.

Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Respiratory protection

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any

hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Consider double gloving. Take note that the product is

flammable, which may impact the selection of hand

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 4019096-00019 Date of first issue: 02/25/2019

protection.

Eye protection : Wear safety glasses with side shields or goggles.

If the work environment or activity involves dusty conditions,

mists or aerosols, wear the appropriate goggles.

Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or

aerosols.

Skin and body protection : Work uniform or laboratory coat.

Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces.

Use appropriate degowning techniques to remove potentially

contaminated clothing.

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the

use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aqueous solution

Color : light brown, yellow

Odor : No data available

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : 129 °F / 54 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower : No data available

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 06/17/2025 4019096-00019 Date of first issue: 02/25/2019 6.0

flammability limit

Vapor pressure No data available

Relative vapor density No data available

Relative density No data available

Density 0.820 - 0.900 g/cm3

Solubility(ies)

Water solubility No data available

Partition coefficient: n-

octanol/water

Not applicable

Autoignition temperature No data available

Decomposition temperature No data available

Viscosity

Viscosity, kinematic No data available

Explosive properties Not explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

Molecular weight No data available

Particle characteristics

Particle size Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity Not classified as a reactivity hazard. Chemical stability Stable under normal conditions. Flammable liquid and vapor.

Possibility of hazardous reac-

tions

Vapors may form explosive mixture with air.

Can react with strong oxidizing agents.

Conditions to avoid Heat, flames and sparks.

Incompatible materials Oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 4019096-00019 Date of first issue: 02/25/2019

Ingestion Eye contact

Acute toxicity

Harmful if swallowed. Toxic in contact with skin.

Product:

Acute oral toxicity : Acute toxicity estimate: 404.59 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 402.36 mg/kg

Method: Calculation method

Components:

Paraffin oil:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Xylene:

Acute oral toxicity : LD50 (Rat): 3,523 mg/kg

Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : LC50 (Rat): 27.571 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 4,200 mg/kg

Flumethrin:

Acute oral toxicity : LD50 (Rat): > 20 mg/kg

LD50 (Mouse): > 20 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2,934 mg/l

Acute dermal toxicity : LD50 (Rat): > 5 mg/kg

Toluene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 28.1 mg/l

Exposure time: 4 h

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 4019096-00019 Date of first issue: 02/25/2019

Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

Paraffin oil:

Species : Rabbit

Result : No skin irritation

Xylene:

Species : Rabbit Result : Skin irritation

Flumethrin:

Result : No skin irritation

Toluene:

Species : Rabbit

Method : Directive 67/548/EEC, Annex V, B.4.

Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Paraffin oil:

Species : Rabbit

Result : No eye irritation

Xylene:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Flumethrin:

Result : Mild eye irritation

Toluene:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 4019096-00019 Date of first issue: 02/25/2019

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Xylene:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact
Species : Mouse
Result : negative

Toluene:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig

Method : Directive 67/548/EEC, Annex V, B.6.

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Xylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-

malian cells Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Species: Mouse

Application Route: Skin contact

Result: negative

Flumethrin:

Genotoxicity in vitro : Test Type: Microbial mutagenesis assay (Ames test)

Test system: Salmonella typhimurium

Result: equivocal

Test Type: Chromosomal aberration

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 4019096-00019 Date of first issue: 02/25/2019

Test system: Chinese hamster ovary cells

Result: positive

Remarks: Not classified due to inconclusive data.

Test Type: Chromosomal aberration Test system: Human lymphocytes

Result: negative

Test Type: in vitro micronucleus test

Test system: Mouse Result: negative

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

Toluene:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: Intraperitoneal injection

Result: negative

Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Species: Mouse

Application Route: inhalation (vapor) Method: OECD Test Guideline 478

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Xylene:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Flumethrin:

Species : Rat
Application Route : Oral
Exposure time : 2 Years

NOAEL : 0.5 mg/kg body weight

Result : negative

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 4019096-00019 Date of first issue: 02/25/2019

Carcinogenicity - Assess-

ment

Weight of evidence does not support classification as a car-

cinogen

Toluene:

Species : Rat

Application Route : inhalation (vapor)
Exposure time : 103 weeks
Result : negative

Species : Mouse
Application Route : Skin contact
Exposure time : 24 Months
Result : negative

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

May damage the unborn child.

Components:

Xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapor)

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: inhalation (vapor)

Result: negative

Flumethrin:

Effects on fetal development : Test Type: Development

Species: Rat

Application Route: Oral

Developmental Toxicity: NOAEL: 0.36 mg/kg body weight Result: Maternal toxicity observed., Reduced offspring weight

gain., Fetal abnormalities.

Test Type: Development

Species: Rat

Application Route: Oral

Developmental Toxicity: NOAEL: 0.5 mg/kg body weight Result: Maternal toxicity observed., Skeletal malformations.,

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 4019096-00019 Date of first issue: 02/25/2019

Reduced fetal weight.

Test Type: Development

Species: Rabbit Application Route: Oral

Developmental Toxicity: NOAEL: 1.7 mg/kg body weight

Result: No teratogenic potential.

Reproductive toxicity - As-

sessment

: May damage the unborn child.

Toluene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapor) Method: OECD Test Guideline 416

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: inhalation (vapor)

Result: positive

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on development, based on

animal experiments.

STOT-single exposure

Causes damage to organs if swallowed.

Components:

Xylene:

Assessment : May cause respiratory irritation.

Flumethrin:

Routes of exposure : Oral

Assessment : Causes damage to organs.

Toluene:

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure if swallowed.

May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Components:

Xylene:

Routes of exposure : inhalation (vapor)
Target Organs : Auditory system

Assessment : Shown to produce significant health effects in animals at con-

centrations of >0.2 to 1 mg/l/6h/d.

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 06/17/2025 4019096-00019 Date of first issue: 02/25/2019 6.0

Flumethrin:

: Oral Routes of exposure

Assessment : Causes damage to organs through prolonged or repeated

exposure.

Toluene:

Target Organs Assessment Inhalation

: Central nervous system

: May cause damage to organs through prolonged or repeated

exposure.

Repeated dose toxicity

Components:

Paraffin oil:

LOAEL : Rat, female
Application Route : Ingestion
Exposure time : QO December 1 : Rat, female

Xylene:

: Rat Species

Species : Rat
LOAEL : > 0.2 - 1 m
Application Route : inhalation (
Exposure time : 13 Weeks
Remarks : Based on (: > 0.2 - 1 mg/l: inhalation (vapor)

Remarks : Based on data from similar materials

Species: RatLOAEL: 150 mg/kgApplication Route: IngestionExposure time: 90 Days : 150 mg/kg

Flumethrin:

Species : Rat Application Route
Exposure time
Target Organs
Symptoms : 0.7 mg/kg : Oral 13 Weeks

: digestive system, Skin

Symptoms decrease in appetite, Skin disorders

: Dog Species

Species :

NOAEL :

Application Route :

Exposure time :

Target Organs :

Symptoms : 0.88 mg/kg Oral 13 Weeks

digestive system, Hair, Skin

decrease in appetite, Skin disorders Symptoms

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 4019096-00019 Date of first issue: 02/25/2019

Toluene:

Species : Rat
LOAEL : 1.875 mg/l
Application Route : inhalation (vapor)

Exposure time : 6 Months

Species : Rat

NOAEL : 625 mg/kg

Application Route : Ingestion

Exposure time : 13 Weeks

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Paraffin oil:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Toluene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Experience with human exposure

Components:

Toluene:

Inhalation : Target Organs: Central nervous system Symptoms: Neurological disorders

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Paraffin oil:

Toxicity to fish : LL50 (Scophthalmus maximus (turbot)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Acartia tonsa (Calanoid copepod)): > 100 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 06/17/2025 4019096-00019 Date of first issue: 02/25/2019 6.0

Remarks: Based on data from similar materials

Toxicity to algae/aquatic EL50 (Skeletonema costatum (marine diatom)): > 100 mg/l

plants Exposure time: 72 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

NOELR (Skeletonema costatum (marine diatom)): > 1 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Xylene:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 13.5 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l

Exposure time: 24 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC50 (Skeletonema costatum (marine diatom)): 10 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic tox-

icity)

NOEC (Danio rerio (zebra fish)): > 0.1 - < 1 mg/l

Exposure time: 35 d

Method: OECD Test Guideline 210

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

EL10 (Daphnia magna (Water flea)): > 1 - 10 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

: NOEC: > 100 mg/l Toxicity to microorganisms

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Flumethrin:

icity)

Toxicity to fish (Chronic tox- : NOEC (Danio rerio (zebra fish)): 0.046 mg/l

Exposure time: 144 h

Toluene:

Toxicity to fish LC50 (Oncorhynchus kisutch (coho salmon)): 5.5 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Ceriodaphnia dubia (water flea)): 3.78 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

NOEC (Skeletonema costatum (marine diatom)): 10 mg/l

Exposure time: 72 h

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 06/17/2025 4019096-00019 Date of first issue: 02/25/2019 6.0

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus kisutch (coho salmon)): 1.39 mg/l

NOEC (Ceriodaphnia dubia (water flea)): 0.74 mg/l

Exposure time: 40 d

Exposure time: 7 d

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

Toxicity to microorganisms EC50 (Nitrosomonas sp.): 84 mg/l

Exposure time: 24 h

Persistence and degradability

Components:

Xylene:

Biodegradability Result: Readily biodegradable.

Biodegradation: > 70 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Toluene:

Biodegradability Result: Readily biodegradable.

Biodegradation: 80 % Exposure time: 20 d

Bioaccumulative potential

Components:

Paraffin oil:

Partition coefficient: n-

octanol/water

 $\log Pow: > 4$

Remarks: Calculation

Xylene:

Partition coefficient: n-

octanol/water

: log Pow: 3.16

Remarks: Calculation

Flumethrin:

Partition coefficient: n-

octanol/water

log Pow: 6.2

Toluene:

Bioaccumulation Species: Leuciscus idus (Golden orfe)

Bioconcentration factor (BCF): 90

Partition coefficient: n-

octanol/water

log Pow: 2.73

Mobility in soil No data available

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 4019096-00019 Date of first issue: 02/25/2019

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or

death.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1992

Proper shipping name : FLAMMABLE LIQUID, TOXIC, N.O.S.

(Xylene, Flumethrin)

Class : 3
Subsidiary risk : 6.1
Packing group : III
Labels : 3 (6.1)
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1992

Proper shipping name : Flammable liquid, toxic, n.o.s.

(Xylene, Flumethrin)

Class : 3 Subsidiary risk : 6.1

Packing group : III

Labels : Flammable Liquids, Toxic

Packing instruction (cargo : :

aircraft)

Packing instruction (passen: 355

ger aircraft)

IMDG-Code

UN number : UN 1992

Proper shipping name : FLAMMABLE LIQUID, TOXIC, N.O.S.

(Xylene, Flumethrin)

Class : 3
Subsidiary risk : 6.1
Packing group : III
Labels : 3 (6.1)
EmS Code : F-E, S-D
Marine pollutant : no

20 / 24

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 4019096-00019 Date of first issue: 02/25/2019

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1992

Proper shipping name : Flammable liquids, toxic, n.o.s.

(Xylene, Flumethrin)

Class : 3
Subsidiary risk : 6.1
Packing group : III

Labels : FLAMMABLE LIQUID, TOXIC

ERG Code : 131 Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Xylene	1330-20-7	100	863
Toluene	108-88-3	1000	163988

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure)

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Xylene 1330-20-7 >= 10 - < 20 %

US State Regulations

Pennsylvania Right To Know

Paraffin oil 8012-95-1 Glycerides, mixed decanoyl and octanoyl 73398-61-5

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 4019096-00019 Date of first issue: 02/25/2019

Xylene 1330-20-7 Toluene 108-88-3

California Prop. 65

WARNING: This product can expose you to chemicals including Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Paraffin oil 8012-95-1 Xylene 1330-20-7

California Permissible Exposure Limits for Chemical Contaminants

Paraffin oil 8012-95-1 Xylene 1330-20-7

The ingredients of this product are reported in the following inventories:

AICS : not determined


DSL : not determined

IECSC : not determined

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 4019096-00019 Date of first issue: 02/25/2019

its for Air Contaminants

OSHA Z-2 : USA. Occupational Exposure Limits (OSHA) - Table Z-2

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-2 / TWA : 8-hour time weighted average OSHA Z-2 / CEIL : Acceptable ceiling concentration

OSHA Z-2 / Peak : Acceptable maximum peak above the acceptable ceiling con-

centration for an 8-hr shift

AIIC - Australian Inventory of Industrial Chemicals: ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

Data Sheet

cy, http://echa.europa.eu/

Revision Date : 06/17/2025

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 4019096-00019 Date of first issue: 02/25/2019

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8