according to the OSHA Hazard Communication Standard



Ethion Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 06/17/2025 10597660-00010 Date of first issue: 01/28/2022 5.0

SECTION 1. IDENTIFICATION

Product name Ethion Formulation

Manufacturer or supplier's details

Company name of supplier Merck & Co., Inc Address 126 E. Lincoln Avenue

Rahway, New Jersey U.S.A. 07065

Telephone 908-740-4000 Emergency telephone 1-908-423-6000

E-mail address EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use Pharmaceutical Not applicable Restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity (Oral) Category 2

Acute toxicity (Inhalation) Category 3

Acute toxicity (Dermal) Category 2

Serious eye damage Category 1

Specific target organ toxicity

- single exposure

Category 1 (Central nervous system)

Specific target organ toxicity : Category 1 (Central nervous system)

- repeated exposure

Other hazards

None known. **GHS** label elements

Hazard pictograms







Signal Word Danger

Hazard Statements H300 + H310 Fatal if swallowed or in contact with skin.

H318 Causes serious eye damage.

H331 Toxic if inhaled.

H370 Causes damage to organs (Central nervous system). H372 Causes damage to organs (Central nervous system)

through prolonged or repeated exposure.

according to the OSHA Hazard Communication Standard



Ethion Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 06/17/2025 10597660-00010 Date of first issue: 01/28/2022 5.0

ments

Supplemental Hazard State: Corrosive to the respiratory tract.

Precautionary Statements

Prevention:

P260 Do not breathe mist or vapors.

P262 Do not get in eyes, on skin, or on clothing. P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, protective clothing, eye protection

and face protection.

Response:

P301 + P310 + P330 IF SWALLOWED: Immediately call a

POISON CENTER. Rinse mouth.

P304 + P340 + P311 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Call a doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER.

P314 Get medical attention if you feel unwell.

P352 + P310 Wash with plenty of soap and water. Immediately

call a POISON CENTER.

P361 + P364 Take off immediately all contaminated clothing and

wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Ethion	563-12-2*	>= 80 - <= 100	TSC
Alcohols, C11-14-iso-, C13-rich, ethoxylated	78330-21-9*	>= 1 - <= 5	TSC

^{*} Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

according to the OSHA Hazard Communication Standard



Ethion Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 06/17/2025 10597660-00010 Date of first issue: 01/28/2022 5.0

General advice In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

If inhaled If inhaled, remove to fresh air.

> If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Get medical attention.

In case of contact, immediately flush skin with plenty of water In case of skin contact

for at least 15 minutes while removing contaminated clothing

and shoes.

Get medical attention immediately. Wash clothing before reuse. Destroy contaminated shoes.

In case of eye contact In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention immediately.

If swallowed If swallowed, DO NOT induce vomiting unless directed to do

so by medical personnel.

Call a physician or poison control center immediately.

Rinse mouth thoroughly with water.

Never give anything by mouth to an unconscious person.

Most important symptoms

and effects, both acute and

delayed

Fatal if swallowed or in contact with skin. Causes serious eye damage.

Toxic if inhaled.

Causes damage to organs.

Causes damage to organs through prolonged or repeated

exposure.

Corrosive to the respiratory tract.

Protection of first-aiders First Aid responders should pay attention to self-protection,

> and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

> Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

Carbon oxides Sulfur oxides

Oxides of phosphorus

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

according to the OSHA Hazard Communication Standard



Ethion Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 5.0 06/17/2025 10597660-00010 Date of first issue: 01/28/2022

Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Evacuate personnel to safe areas.

Only trained personnel should re-enter the area.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Advice on safe handling : Do not get on skin or clothing.

Do not breathe mist or vapors.

Do not swallow. Do not get in eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

according to the OSHA Hazard Communication Standard



Ethion Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 06/17/2025 10597660-00010 Date of first issue: 01/28/2022 5.0

Keep container tightly closed.

Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage Keep in properly labeled containers.

> Store locked up. Keep tightly closed.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Materials to avoid Do not store with the following product types:

Strong oxidizing agents

Self-reactive substances and mixtures

Organic peroxides Flammable liquids Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures which in contact with water emit

flammable gases

Explosives Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethion	563-12-2	TWA	4 μg/m3 (OEB 4)	Internal
	Further information: Skin			
		Wipe limit	40 μg/100 cm2	Internal
		TWA (Inhalable fraction	0.05 mg/m ³	ACGIH
		and vapor)		
		TWA	0.4 mg/m ³	NIOSH REL

Engineering measures

The information below is intended for larger pilot/commercialscale operations and manufacturing. For smaller scale, clinical, or pharmacy settings, site-specific internal risk assessment practices should be conducted to determine appropriate exposure control measures. The health hazard risks of handling this material are dependent on multiple factors, including but not limited to physical form and quantity handled. If applicable, use process enclosures, local exhaust ventilation (e.g., Biosafety Cabinet, Ventilated Balance Enclosures), or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne

levels as low as reasonably achievable.

All engineering controls should be implemented by facility

according to the OSHA Hazard Communication Standard



Ethion Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 5.0 06/17/2025 10597660-00010 Date of first issue: 01/28/2022

design and operated in accordance with GMP principles to

protect products, workers, and the environment.

Essentially no open handling permitted.

Use closed processing systems or containment technologies. If handled in a laboratory, use a properly designed biosafety cabinet, fume hood, or other containment device if the potential exists for aerosolization. If this potential does not exist, handle over lined trays or benchtops.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any

hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Consider double gloving.

Eye protection : Wear safety glasses with side shields or goggles.

If the work environment or activity involves dusty conditions,

mists or aerosols, wear the appropriate goggles.

Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or

aerosols.

Skin and body protection : Work uniform or laboratory coat.

Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces.

Use appropriate degowning techniques to remove potentially

contaminated clothing.

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the

use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

according to the OSHA Hazard Communication Standard



Ethion Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 5.0 06/17/2025 10597660-00010 Date of first issue: 01/28/2022

Color : No data available

Odor : No data available

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Not applicable

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : No data available

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

: Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

according to the OSHA Hazard Communication Standard



Ethion Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 5.0 06/17/2025 10597660-00010 Date of first issue: 01/28/2022

Particle characteristics

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard. Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Conditions to avoid : None known. Incompatible materials : Oxidizing agents

Hazardous decomposition :

products

No hazardous decomposition products are known.

Can react with strong oxidizing agents.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Fatal if swallowed or in contact with skin.

Toxic if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: 14.87 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 0.515 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 70.95 mg/kg

Method: Calculation method

Components:

Ethion:

Acute oral toxicity : LD50 (Rat): 13 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.450 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): 62 mg/kg

Alcohols, C11-14-iso-, C13-rich, ethoxylated:

Acute oral toxicity : LD50 (Rat): > 2,000 - 3,340 mg/kg

according to the OSHA Hazard Communication Standard



Ethion Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 5.0 06/17/2025 10597660-00010 Date of first issue: 01/28/2022

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Ethion:

Species : Rabbit

Result : Mild skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Ethion:

Result : No eye irritation

Alcohols, C11-14-iso-, C13-rich, ethoxylated:

Result : Irreversible effects on the eye

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Ethion:

Routes of exposure : Skin contact Species : Guinea pig Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Ethion:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-

according to the OSHA Hazard Communication Standard



Ethion Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 5.0 06/17/2025 10597660-00010 Date of first issue: 01/28/2022

malian cells Result: negative

Test Type: in vitro micronucleus test

Result: positive

Genotoxicity in vivo : Test Type: Chromosomal aberration

Species: Rat Result: negative

Test Type: In vivo micronucleus test

Species: Mouse Result: positive

Germ cell mutagenicity -

Assessment

: Weight of evidence does not support classification as a germ

cell mutagen.

Carcinogenicity

Not classified based on available information.

Components:

Ethion:

Species : Rat
Application Route : Ingestion
Exposure time : 18 Months
Result : negative

Species : Mouse
Application Route : Ingestion
Exposure time : 24 Months
Result : negative

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Ethion:

Effects on fertility : Test Type: Three-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

according to the OSHA Hazard Communication Standard



Ethion Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 5.0 06/17/2025 10597660-00010 Date of first issue: 01/28/2022

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

STOT-single exposure

Causes damage to organs (Central nervous system).

Corrosive to the respiratory tract.

Components:

Ethion:

Assessment : Causes damage to organs.

STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Components:

Ethion:

Target Organs : Central nervous system

Assessment : Causes damage to organs through prolonged or repeated

exposure.

Repeated dose toxicity

Components:

Ethion:

Species : Dog

NOAEL : 0.05 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

Ethion:

Ingestion : Symptoms: Blurred vision, Dizziness, Headache

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Ethion:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.18 mg/l

Exposure time: 96 h

according to the OSHA Hazard Communication Standard



Ethion Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 06/17/2025 10597660-00010 Date of first issue: 01/28/2022 5.0

Toxicity to daphnia and other : EC50: 0.056 - 7.7 µg/l

aquatic invertebrates

Exposure time: 48 h

Alcohols, C11-14-iso-, C13-rich, ethoxylated:

Toxicity to fish : LC50 : > 1 - 10 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia sp. (Water flea)): > 1 - 10 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: EC50: > 1 - 10 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic tox-:

icity)

NOEC (Pimephales promelas (fathead minnow)): > 0.1 - 1

Exposure time: 30 d

Remarks: Based on data from similar materials

NOEC (Daphnia magna (Water flea)): > 0.1 - 1 mg/l

Toxicity to daphnia and other:

aquatic invertebrates (Chron-

ic toxicity)

Exposure time: 21 d

Remarks: Based on data from similar materials

Persistence and degradability

Components:

Ethion:

Biodegradability : Result: not rapidly degradable

Alcohols, C11-14-iso-, C13-rich, ethoxylated:

Biodegradability : Result: Readily biodegradable.

Bioaccumulative potential

Components:

Ethion:

Partition coefficient: n- : log Pow: 5.07

octanol/water

Mobility in soil No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

according to the OSHA Hazard Communication Standard



Ethion Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 5.0 06/17/2025 10597660-00010 Date of first issue: 01/28/2022

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 2810

Proper shipping name : TOXIC LIQUID, ORGANIC, N.O.S.

(Ethion)

Class : 6.1
Packing group : II
Labels : 6.1
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 2810

Proper shipping name : Toxic liquid, organic, n.o.s.

(Ethion)

Class : 6.1
Packing group : II
Labels : Toxic
Packing instruction (cargo : 662

aircraft)

Packing instruction (passen- : 654

ger aircraft)

IMDG-Code

UN number : UN 2810

Proper shipping name : TOXIC LIQUID, ORGANIC, N.O.S.

(Ethion)

Class : 6.1
Packing group : II
Labels : 6.1
EmS Code : F-A, S-A
Marine pollutant : yes

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 2810

Proper shipping name : Toxic, liquids, organic, n.o.s.

(Ethion)

Class : 6.1
Packing group : II
Labels : TOXIC
ERG Code : 153
Marine pollutant : yes(Ethion)

according to the OSHA Hazard Communication Standard



Ethion Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 5.0 06/17/2025 10597660-00010 Date of first issue: 01/28/2022

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Ethion	563-12-2	10	11

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Ethion	563-12-2	10	11

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

•		•
Components	CAS-No.	Component TPQ (lbs)
Ethion	563-12-2	1000
SARA 311/312 Hazards	: Acute toxicity (any Specific target orga Serious eye damag	in toxicity (single or repeated exposure)

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Ethion 563-12-2
Water 7732-18-5
Alcohols, C11-14-iso-, C13-rich, ethoxylated 78330-21-9

California List of Hazardous Substances

Ethion 563-12-2

California Permissible Exposure Limits for Chemical Contaminants

Ethion 563-12-2

The ingredients of this product are reported in the following inventories:

AICS : not determined

DSL : not determined

IECSC : not determined

according to the OSHA Hazard Communication Standard




Ethion Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 5.0 06/17/2025 10597660-00010 Date of first issue: 01/28/2022

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance: ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory: LC50 - Lethal Concentration to 50 % of a test population: LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office

according to the OSHA Hazard Communication Standard



Ethion Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 5.0 06/17/2025 10597660-00010 Date of first issue: 01/28/2022

of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 06/17/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8