according to the OSHA Hazard Communication Standard



Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 3.0 06/17/2025 10843991-00005 Date of first issue: 09/12/2022

SECTION 1. IDENTIFICATION

Product name : Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc Address : 126 E. Lincoln Avenue

Rahway, New Jersey U.S.A. 07065

Telephone : 908-740-4000 Emergency telephone : 1-908-423-6000

E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization : Category 1

Aspiration hazard : Category 1

Other hazards

Cutaneous sensations may occur, such as burning or stinging on the face and mucosae. However, these sensations cause no lesions and are of a transitory nature (max. 24 hours).

GHS label elements

Hazard pictograms :





Signal Word : Danger

Hazard Statements : H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

Precautionary Statements : Prevention:

P261 Avoid breathing mist or vapors.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear protective gloves.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER.

P302 + P352 IF ON SKIN: Wash with plenty of water.

according to the OSHA Hazard Communication Standard



Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/14/2025

 3.0
 06/17/2025
 10843991-00005
 Date of first issue: 09/12/2022

P331 Do NOT induce vomiting.

P333 + P313 If skin irritation or rash occurs: Get medical atten-

tion.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0*	>= 80 - <= 100	TSC
Permethrin (ISO)	52645-53-1*	>= 0.5 - <= 1.5	TSC
2-(2-Butoxyethoxy)ethyl 6- propylpiperonyl ether	51-03-6*	>= 0.5 - <= 1.5	TSC

^{*} Indicates that the identifier is a CAS No.

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty

of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse. Flush eyes with water as a precaution.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

If vomiting occurs have person lean forward.

Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

TSC- the actual concentration or concentration range is withheld as a trade secret

according to the OSHA Hazard Communication Standard



Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 3.0 06/17/2025 10843991-00005 Date of first issue: 09/12/2022

Most important symptoms

and effects, both acute and

delayed

This product contains a pyrethroid.

Pyrethroid poisoning should not be confused with carbamate

or organophosphate poisoning.

May be fatal if swallowed and enters airways.

May cause an allergic skin reaction.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Vapors may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Carbon oxides

Chlorine compounds

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers)

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for : Soak up with inert absorbent material.

according to the OSHA Hazard Communication Standard



Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 3.0 06/17/2025 10843991-00005 Date of first issue: 09/12/2022

containment and cleaning up For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation. Advice on safe handling : Do not get on skin or clothing.

Avoid breathing mist or vapors.

Do not swallow.

Avoid contact with eyes.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Keep container tightly closed.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store locked up. Keep tightly closed.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
	0.47.40.05.0			400111
Distillates (petroleum), solvent-	64742-65-0	TWA (Inhal-	5 mg/m³	ACGIH
dewaxed heavy paraffinic		able particu-		
		late matter)		
		TWA (Mist)	5 mg/m³	OSHA Z-1
		TWA (Mist)	5 mg/m³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Permethrin (ISO)	52645-53-1	TWA	80 μg/m3 (OEB 3)	Internal
		Wipe limit	800 μg/100 cm ²	Internal

according to the OSHA Hazard Communication Standard



Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

Version Date of last issue: 04/14/2025 Revision Date: SDS Number: 06/17/2025 10843991-00005 Date of first issue: 09/12/2022 3.0

2-(2-Butoxyethoxy)ethyl 6-51-03-6 **TWA** 4 mg/m3 (OEB 1) Internal propylpiperonyl ether

Engineering measures Use appropriate engineering controls and manufacturing

technologies to control airborne concentrations (e.g., drip-

less quick connections).

All engineering controls should be implemented by facility design and operated in accordance with GMP principles to

protect products, workers, and the environment.

Containment technologies suitable for controlling compounds are required to control at source and to prevent migration of

the compound to uncontrolled areas (e.g., open-face containment devices). Minimize open handling.

Personal protective equipment

Respiratory protection General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where

concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and

use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any

hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material Chemical-resistant gloves

Remarks Consider double gloving.

Wear safety glasses with side shields or goggles. Eye protection

If the work environment or activity involves dusty conditions,

mists or aerosols, wear the appropriate goggles.

Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or

aerosols.

Work uniform or laboratory coat. Skin and body protection

> Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces.

Use appropriate degowning techniques to remove potentially

contaminated clothing.

If exposure to chemical is likely during typical use, provide Hygiene measures

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke.

Contaminated work clothing should not be allowed out of the

Wash contaminated clothing before re-use.

according to the OSHA Hazard Communication Standard



Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 3.0 06/17/2025 10843991-00005 Date of first issue: 09/12/2022

The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : amber

clear

Odor : odorless

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling :

range

No data available

Flash point : 199.9 °F / 93.3 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : < 2 mmHg (77 °F / 25 °C)

Relative vapor density : No data available

Relative density : 0.840 - 0.890 (68 °F / 20 °C)

Density : No data available

Solubility(ies)

Water solubility : negligible

Partition coefficient: n-

octanol/water

: Not applicable

according to the OSHA Hazard Communication Standard



Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 3.0 06/17/2025 10843991-00005 Date of first issue: 09/12/2022

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : 25 - 40 mm²/s

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle characteristics

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard. Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Vapors may form explosive mixture with air. Can react with strong oxidizing agents.

Conditions to avoid : None known.
Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

according to the OSHA Hazard Communication Standard



Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 3.0 06/17/2025 10843991-00005 Date of first issue: 09/12/2022

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials

Permethrin (ISO):

Acute oral toxicity : LD50 (Rat): 480 - 554 mg/kg

Acute inhalation toxicity : LC50 (Rat): 2.3 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

2-(2-Butoxyethoxy)ethyl 6-propylpiperonyl ether:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 423

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Rabbit

Result : No skin irritation

Remarks : Based on data from similar materials

according to the OSHA Hazard Communication Standard



Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 3.0 06/17/2025 10843991-00005 Date of first issue: 09/12/2022

Permethrin (ISO):

Species : Rabbit

Result : No skin irritation

2-(2-Butoxyethoxy)ethyl 6-propylpiperonyl ether:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Permethrin (ISO):

Species : Rabbit

Result : No eye irritation

2-(2-Butoxyethoxy)ethyl 6-propylpiperonyl ether:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Remarks : Based on data from similar materials

according to the OSHA Hazard Communication Standard



Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 3.0 06/17/2025 10843991-00005 Date of first issue: 09/12/2022

Permethrin (ISO):

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : positive

Assessment : Probability or evidence of skin sensitization in humans

2-(2-Butoxyethoxy)ethyl 6-propylpiperonyl ether:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Permethrin (ISO):

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

Result: negative

Test Type: Chromosome aberration test in vitro

Result: positive

according to the OSHA Hazard Communication Standard



Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 3.0 06/17/2025 10843991-00005 Date of first issue: 09/12/2022

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Mouse Result: negative

Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Species: Mouse Result: negative

Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: Intraperitoneal injection

Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Mouse

Application Route: Ingestion

Result: positive

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

2-(2-Butoxyethoxy)ethyl 6-propylpiperonyl ether:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Mouse
Application Route : Skin contact
Exposure time : 78 weeks

Method : OECD Test Guideline 451

Result : negative

Permethrin (ISO):

Species : Rat Result : negative

Species : Mouse

according to the OSHA Hazard Communication Standard



Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 3.0 06/17/2025 10843991-00005 Date of first issue: 09/12/2022

Result : negative

2-(2-Butoxyethoxy)ethyl 6-propylpiperonyl ether:

Species : Rat
Application Route : Ingestion
Exposure time : 107 weeks

Method : OECD Test Guideline 451

Result : negative

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Skin contact Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

Permethrin (ISO):

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Result: negative

according to the OSHA Hazard Communication Standard



Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 3.0 06/17/2025 10843991-00005 Date of first issue: 09/12/2022

2-(2-Butoxyethoxy)ethyl 6-propylpiperonyl ether:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

STOT-single exposure

Not classified based on available information.

Components:

2-(2-Butoxyethoxy)ethyl 6-propylpiperonyl ether:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Rabbit

NOAEL : 1,000 mg/kg

Application Route : Skin contact

Exposure time : 4 Weeks

Method : OECD Test Guideline 410

Remarks : Based on data from similar materials

Species : Rat

NOAEL : > 980 mg/m³

Application Route : inhalation (dust/mist/fume)

Exposure time : 4 Weeks

Remarks : Based on data from similar materials

Permethrin (ISO):

Species : Rat

NOAEL : 0.2201 mg/l
Application Route : Inhalation
Exposure time : 90 Days

Species : Rat

NOAEL : 175 mg/kg Application Route : Ingestion Exposure time : 90 Days

according to the OSHA Hazard Communication Standard



Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

Version Date of last issue: 04/14/2025 Revision Date: SDS Number: 06/17/2025 10843991-00005 Date of first issue: 09/12/2022 3.0

2-(2-Butoxyethoxy)ethyl 6-propylpiperonyl ether:

Species Rat

NOAEL 1,323 mg/kg Application Route Ingestion Exposure time 7 Weeks

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

EC50 (Pseudokirchneriella subcapitata (green algae)): > 100

Toxicity to algae/aquatic

mg/l

plants

ic toxicity)

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other:

aquatic invertebrates (Chron-

NOEC (Daphnia magna (Water flea)): 10 mg/l Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Toxicity to microorganisms NOEC: > 1.93 mg/l

Exposure time: 10 min Method: DIN 38 412 Part 8

Remarks: Based on data from similar materials

Permethrin (ISO):

Toxicity to fish LC50 (Lepomis macrochirus (Bluegill sunfish)): 0.00079 mg/l

according to the OSHA Hazard Communication Standard



Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

Version Date of last issue: 04/14/2025 Revision Date: SDS Number: 06/17/2025 10843991-00005 Date of first issue: 09/12/2022 3.0

Exposure time: 96 h

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.0001 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 1.13

ma/l

Exposure time: 72 h

EC10 (Pseudokirchneriella subcapitata (green algae)): 0.0023

mg/l

Exposure time: 72 h

Toxicity to fish (Chronic tox-

icity)

NOEC (Danio rerio (zebra fish)): 0.00041 mg/l

Exposure time: 35 d

Method: OECD Test Guideline 210

Toxicity to daphnia and other: aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.0047 µg/l Exposure time: 21 d

Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: > 1,000 mg/l

Exposure time: 3 h

2-(2-Butoxyethoxy)ethyl 6-propylpiperonyl ether:

Toxicity to fish LC50 (Cyprinodon variegatus (sheepshead minnow)): 3.94

ma/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.51 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): 3.89

ma/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.824

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOEC (Pimephales promelas (fathead minnow)): 0.18 mg/l

Exposure time: 35 d

Toxicity to daphnia and other: aguatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.03 mg/l

Exposure time: 21 d

Toxicity to microorganisms

EC50: > 1,000 mg/lExposure time: 3 h

according to the OSHA Hazard Communication Standard



Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 3.0 06/17/2025 10843991-00005 Date of first issue: 09/12/2022

Method: OECD Test Guideline 209

Persistence and degradability

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 2 - 8 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Permethrin (ISO):

Biodegradability : Result: Not readily biodegradable.

Method: OECD Test Guideline 301F

2-(2-Butoxyethoxy)ethyl 6-propylpiperonyl ether:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 301D

Bioaccumulative potential

Components:

Permethrin (ISO):

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)

Bioconcentration factor (BCF): 570

Partition coefficient: n-

octanol/water

: log Pow: 4.67

2-(2-Butoxyethoxy)ethyl 6-propylpiperonyl ether:

Partition coefficient: n-

octanol/water

: log Pow: 5

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

according to the OSHA Hazard Communication Standard



Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

Version SDS Number: Date of last issue: 04/14/2025 Revision Date: 06/17/2025 10843991-00005 Date of first issue: 09/12/2022 3.0

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number UN 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Permethrin (ISO), 2-(2-butoxyethoxy)ethyl 6-propylpiperonyl

ether)

Class 9 Packing group Ш Labels 9 Environmentally hazardous yes

IATA-DGR

UN/ID No. UN 3082

Proper shipping name Environmentally hazardous substance, liquid, n.o.s.

(Permethrin (ISO), 2-(2-Butoxyethoxy)ethyl 6-propylpiperonyl

ether)

Class 9 Packing group Ш

Miscellaneous Labels

Packing instruction (cargo 964

aircraft)

Packing instruction (passen-

ger aircraft)

964

Environmentally hazardous

yes

IMDG-Code

UN number UN 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Permethrin (ISO), 2-(2-Butoxyethoxy)ethyl 6-propylpiperonyl

ether)

Class 9 Packing group Ш Labels 9 **EmS Code** F-A, S-F Marine pollutant yes

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN 3082 UN/ID/NA number

Proper shipping name Environmentally hazardous substance, liquid, n.o.s.

(Permethrin (ISO), 2-(2-Butoxyethoxy)ethyl 6-propylpiperonyl

ether)

Class 9

according to the OSHA Hazard Communication Standard



Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 3.0 06/17/2025 10843991-00005 Date of first issue: 09/12/2022

Packing group : III

Labels : CLASS 9 ERG Code : 171

Marine pollutant : yes(Permethrin (ISO), 2-(2-Butoxyethoxy)ethyl 6-

propylpiperonyl ether)

Remarks : Above applies only to containers over 119 gallons or 450

liters

Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO. Above applies only to containers over 119 gallons or 450

liters.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization

Aspiration hazard

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Permethrin (ISO) 52645-53-1 >= 1 - < 5 %

2-(2- 51-03-6 >= 1 - < 5 %

Butoxyethoxy)ethyl 6propylpiperonyl

ether

US State Regulations

Pennsylvania Right To Know

Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0

California List of Hazardous Substances

Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0

according to the OSHA Hazard Communication Standard



Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 3.0 06/17/2025 10843991-00005 Date of first issue: 09/12/2022

California Permissible Exposure Limits for Chemical Contaminants

Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0

The ingredients of this product are reported in the following inventories:

AICS : not determined

DSL : not determined

IECSC : not determined

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:

Health 2 0 Instability

Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Sub-

according to the OSHA Hazard Communication Standard



Permethrin (1%) / Piperonyl Butoxide (1%) Formulation (BR)

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 3.0 06/17/2025 10843991-00005 Date of first issue: 09/12/2022

stances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States): UN - United Nations: UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 06/17/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8