

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bovilis MH Single Shot RTU / MH + IBR Formulation

Version 7.0      Revision Date: 06/17/2025      SDS Number: 10876233-00015      Date of last issue: 04/14/2025  
Date of first issue: 10/24/2022

### SECTION 1. IDENTIFICATION

Product name : Bovilis MH Single Shot RTU / MH + IBR Formulation  
Other means of identification : Coopers Bovilis MH Single-Shot RTU READY-TO-USE MH VACCINE FOR CATTLE (92022)  
COOPERS BOVILIS MH+IBR BOVINE RESPIRATORY DISEASE (BRD) VACCINE (64608)  
Bovilis MH+IBR (A011518)  
COOPERS BOVILIS MH MANNHEIMIA HAEMOLYTICA VACCINE FOR CATTLE (55767)

#### Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc  
Address : 126 E. Lincoln Avenue  
Rahway, New Jersey U.S.A. 07065  
Telephone : 908-740-4000  
Emergency telephone : 1-908-423-6000  
E-mail address : EHSDATASTEWARD@merck.com

#### Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product  
Restrictions on use : Not applicable

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization : Category 1  
Carcinogenicity : Category 1B

#### Other hazards

None known.

#### GHS label elements

Hazard pictograms :

Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.  
H350 May cause cancer.

Precautionary Statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bovilis MH Single Shot RTU / MH + IBR Formulation

Version 7.0      Revision Date: 06/17/2025      SDS Number: 10876233-00015      Date of last issue: 04/14/2025  
Date of first issue: 10/24/2022

P261 Avoid breathing mist or vapors.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves, protective clothing, eye protection and face protection.

### Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.  
P308 + P313 IF exposed or concerned: Get medical attention.  
P333 + P313 If skin irritation or rash occurs: Get medical attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

### Storage:

P405 Store locked up.

### Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Antigen	-	>= 45 - <= 70	TSC
White mineral oil (petroleum)	8042-47-5*	>= 7 - <= 13	TSC
Glycerine	56-81-5*	>= 0.5 - <= 1.5	TSC
Formaldehyde	50-00-0*	>= 0.1 - <= 1	TSC

\* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.  
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.  
Remove contaminated clothing and shoes.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bovilis MH Single Shot RTU / MH + IBR Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2025
7.0	06/17/2025	10876233-00015	Date of first issue: 10/24/2022

In case of eye contact	:	Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse. Flush eyes with water as a precaution.
If swallowed	:	Get medical attention if irritation develops and persists. If swallowed, DO NOT induce vomiting. Get medical attention. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	:	May cause an allergic skin reaction. May cause cancer.
Protection of first-aiders	:	First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
Notes to physician	:	Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO <sub>2</sub> ) Dry chemical
Unsuitable extinguishing media	:	None known.
Specific hazards during fire fighting	:	Exposure to combustion products may be a hazard to health.
Hazardous combustion products	:	Carbon oxides
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
Environmental precautions	:	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g., by containment or oil barriers).

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bovilis MH Single Shot RTU / MH + IBR Formulation

Version 7.0      Revision Date: 06/17/2025      SDS Number: 10876233-00015      Date of last issue: 04/14/2025  
Date of first issue: 10/24/2022

Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.  
Avoid breathing mist or vapors.  
Do not swallow.  
Avoid contact with eyes.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep container tightly closed.  
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.  
Store locked up.  
Keep tightly closed.  
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Self-reactive substances and mixtures  
Organic peroxides  
Explosives  
Gases

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
------------	---------	------------	-----------------	-------

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bovilis MH Single Shot RTU / MH + IBR Formulation

Version 7.0      Revision Date: 06/17/2025      SDS Number: 10876233-00015      Date of last issue: 04/14/2025  
Date of first issue: 10/24/2022

		(Form of exposure)	ters / Permissible concentration	
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH
		TWA (Mist)	5 mg/m <sup>3</sup>	NIOSH REL
		ST (Mist)	10 mg/m <sup>3</sup>	NIOSH REL
Formaldehyde	50-00-0	TWA	0.1 ppm	ACGIH
		STEL	0.3 ppm	ACGIH
		TWA	0.016 ppm	NIOSH REL
		C	0.1 ppm	NIOSH REL
		PEL	0.75 ppm	OSHA CARC
		STEL	2 ppm	OSHA CARC
		TWA	0.016 ppm (Formaldehyde)	NIOSH REL

**Engineering measures** : Use appropriate engineering controls and manufacturing technologies to control airborne concentrations (e.g., drip-less quick connections).  
All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment.  
Laboratory operations do not require special containment.

### Personal protective equipment

**Respiratory protection** : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

**Hand protection**  
**Material** : Chemical-resistant gloves

**Eye protection** : Wear safety glasses with side shields or goggles.  
If the work environment or activity involves dusty conditions, mists or aerosols, wear the appropriate goggles.  
Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or aerosols.

**Skin and body protection** : Work uniform or laboratory coat.  
**Hygiene measures** : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bovilis MH Single Shot RTU / MH + IBR Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2025
7.0	06/17/2025	10876233-00015	Date of first issue: 10/24/2022

When using do not eat, drink or smoke.  
Contaminated work clothing should not be allowed out of the workplace.  
Wash contaminated clothing before re-use.  
The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the use of administrative controls.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	suspension
Color	:	white to off-white
Odor	:	odorless
Odor Threshold	:	No data available
pH	:	6.0 - 8.0
Melting point/freezing point	:	32 °F / 0 °C
Initial boiling point and boiling range	:	212 °F / 100 °C (1000 hPa)
Flash point	:	No data available
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	2.37 kPa (68 °F / 20 °C)
Relative vapor density	:	No data available
Relative density	:	1
Density	:	No data available
Solubility(ies) Water solubility	:	soluble
Partition coefficient: n-	:	Not applicable

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bovilis MH Single Shot RTU / MH + IBR Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2025
7.0	06/17/2025	10876233-00015	Date of first issue: 10/24/2022

octanol/water	
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Molecular weight	: No data available
Particle characteristics	
Particle size	: Not applicable

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Can react with strong oxidizing agents.
Conditions to avoid	: None known.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate: > 20000 ppm Exposure time: 4 h Test atmosphere: gas Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate: > 5,000 mg/kg

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bovilis MH Single Shot RTU / MH + IBR Formulation

Version 7.0      Revision Date: 06/17/2025      SDS Number: 10876233-00015      Date of last issue: 04/14/2025  
Date of first issue: 10/24/2022

Method: Calculation method

### Components:

#### **White mineral oil (petroleum):**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity  
Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

#### **Glycerine:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Acute dermal toxicity : LD50 (Guinea pig): > 5,000 mg/kg

#### **Formaldehyde:**

Acute oral toxicity : Acute toxicity estimate: 100 mg/kg  
Method: Expert judgment  
Remarks: Based on national or regional regulation.  
Acute inhalation toxicity : Acute toxicity estimate (Rat): 100 ppm  
Exposure time: 4 h  
Test atmosphere: gas  
Method: Expert judgment  
Acute dermal toxicity : LD50 (Rabbit): 270 mg/kg

#### **Skin corrosion/irritation**

Not classified based on available information.

### Components:

#### **White mineral oil (petroleum):**

Species : Rabbit  
Result : No skin irritation

#### **Glycerine:**

Species : Rabbit  
Result : No skin irritation

#### **Formaldehyde:**

Result : Corrosive after 3 minutes to 1 hour of exposure

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bovilis MH Single Shot RTU / MH + IBR Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2025
7.0	06/17/2025	10876233-00015	Date of first issue: 10/24/2022

Remarks : Based on national or regional regulation.

### Serious eye damage/eye irritation

Not classified based on available information.

### Components:

#### White mineral oil (petroleum):

Species	: Rabbit
Result	: No eye irritation

#### Glycerine:

Species	: Rabbit
Result	: No eye irritation

#### Formaldehyde:

Result	: Irreversible effects on the eye
Remarks	: Based on skin corrosivity.

### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### Respiratory sensitization

Not classified based on available information.

### Components:

#### White mineral oil (petroleum):

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: negative

#### Formaldehyde:

Test Type	: Human repeat insult patch test (HRIPT)
Routes of exposure	: Skin contact
Species	: Humans
Result	: positive

Assessment	: Probability or evidence of high skin sensitization rate in humans
------------	---

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### White mineral oil (petroleum):

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bovilis MH Single Shot RTU / MH + IBR Formulation

Version 7.0	Revision Date: 06/17/2025	SDS Number: 10876233-00015	Date of last issue: 04/14/2025 Date of first issue: 10/24/2022
----------------	------------------------------	-------------------------------	---

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: negative Remarks: Based on data from similar materials

### Glycerine:

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Result: negative  Test Type: Bacterial reverse mutation assay (AMES) Result: negative  Test Type: Chromosome aberration test in vitro Result: negative  Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro) Result: negative
-----------------------	--

### Formaldehyde:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: positive  Test Type: In vitro mammalian cell gene mutation test Result: positive  Test Type: Chromosome aberration test in vitro Result: positive
Genotoxicity in vivo	: Test Type: In vivo mammalian alkaline comet assay Species: Mouse Application Route: Inhalation Result: positive
Germ cell mutagenicity - Assessment	: Positive result(s) from in vivo mammalian somatic cell mutagenicity tests.

### Carcinogenicity

May cause cancer.

### Components:

#### White mineral oil (petroleum):

Species	: Rat
Application Route	: Ingestion

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bovilis MH Single Shot RTU / MH + IBR Formulation

Version 7.0      Revision Date: 06/17/2025      SDS Number: 10876233-00015      Date of last issue: 04/14/2025  
Date of first issue: 10/24/2022

Exposure time : 24 Months  
Result : negative

### Glycerine:

Species : Rat  
Application Route : Ingestion  
Exposure time : 2 Years  
Result : negative

### Formaldehyde:

Species : Rat  
Application Route : inhalation (gas)  
Exposure time : 28 Months  
Result : positive

Carcinogenicity - Assessment : Sufficient evidence of carcinogenicity in animal experiments

**IARC**      Group 1: Carcinogenic to humans  
Formaldehyde      50-00-0

**OSHA**      OSHA specifically regulated carcinogen  
Formaldehyde      50-00-0

**NTP**      Known to be human carcinogen  
Formaldehyde      50-00-0

### Reproductive toxicity

Not classified based on available information.

### Components:

#### White mineral oil (petroleum):

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Skin contact  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

### Glycerine:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bovilis MH Single Shot RTU / MH + IBR Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2025
7.0	06/17/2025	10876233-00015	Date of first issue: 10/24/2022

Application Route: Ingestion  
Result: negative

### Formaldehyde:

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (gas)  
Result: negative

### STOT-single exposure

Not classified based on available information.

### Components:

#### Formaldehyde:

Assessment : May cause respiratory irritation.

### STOT-repeated exposure

Not classified based on available information.

### Repeated dose toxicity

### Components:

#### White mineral oil (petroleum):

Species : Rat  
LOAEL : 160 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

Species : Rat  
LOAEL :  $\geq 1$  mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 4 Weeks  
Method : OECD Test Guideline 412

#### Glycerine:

Species : Rat  
NOAEL : 0.167 mg/l  
LOAEL : 0.622 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 13 Weeks

Species : Rat  
NOAEL : 8,000 - 10,000 mg/kg  
Application Route : Ingestion  
Exposure time : 2 y

Species : Rabbit  
NOAEL : 5,040 mg/kg  
Application Route : Skin contact

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bovilis MH Single Shot RTU / MH + IBR Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2025
7.0	06/17/2025	10876233-00015	Date of first issue: 10/24/2022

Exposure time : 45 Weeks

### Aspiration toxicity

Not classified based on available information.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### White mineral oil (petroleum):

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOEC (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l Exposure time: 28 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 1,000 mg/l Exposure time: 21 d

##### Glycerine:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 54,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 1,955 mg/l Exposure time: 48 h
Toxicity to microorganisms	: NOEC (Pseudomonas putida): > 10,000 mg/l Exposure time: 16 h Method: DIN 38 412 Part 8

##### Formaldehyde:

Toxicity to fish	: LC50 (Morone saxatilis (striped bass)): 6.7 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia pulex (Water flea)): 5.8 mg/l Exposure time: 48 h
Toxicity to algae/aquatic	: ErC50 (Desmodesmus subspicatus (green algae)): 4.89 mg/l

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bovilis MH Single Shot RTU / MH + IBR Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2025
7.0	06/17/2025	10876233-00015	Date of first issue: 10/24/2022

plants	Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 1.04 mg/l Exposure time: 21 d Method: OECD Test Guideline 211
Toxicity to microorganisms	: EC50 (activated sludge): 19 mg/l Exposure time: 3 h Method: OECD Test Guideline 209

### Persistence and degradability

#### Components:

##### **White mineral oil (petroleum):**

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 31 % Exposure time: 28 d
------------------	---

##### **Glycerine:**

Biodegradability	: Result: Readily biodegradable. Biodegradation: 92 % Exposure time: 30 d Method: OECD Test Guideline 301D
------------------	---

##### **Formaldehyde:**

Biodegradability	: Result: Readily biodegradable. Biodegradation: 99 % Exposure time: 28 d Method: OECD Test Guideline 301A
------------------	---

### Bioaccumulative potential

#### Components:

##### **Glycerine:**

Partition coefficient: n-octanol/water	: log Pow: -1.75
--	------------------

##### **Formaldehyde:**

Partition coefficient: n-octanol/water	: log Pow: 0.35 Remarks: Calculation
--	---

### Mobility in soil

No data available

### Other adverse effects

No data available

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bovilis MH Single Shot RTU / MH + IBR Formulation

Version 7.0      Revision Date: 06/17/2025      SDS Number: 10876233-00015      Date of last issue: 04/14/2025  
Date of first issue: 10/24/2022

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.  
Do not dispose of waste into sewer.  
Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to IMO instruments

Not applicable for product as supplied.

#### Domestic regulation

##### 49 CFR

UN/ID/NA number : UN 3082  
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.  
(Formaldehyde)  
Class : 9  
Packing group : III  
Labels : CLASS 9  
ERG Code : 171  
Marine pollutant : no  
Remarks : THE ABOVE INFORMATION ONLY APPLIES TO PACKAGE SIZES WHERE THE HAZARDOUS SUBSTANCE MEETS THE REPORTABLE QUANTITY.

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### SECTION 15. REGULATORY INFORMATION

#### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Formaldehyde	50-00-0	100	33333

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bovilis MH Single Shot RTU / MH + IBR Formulation

Version 7.0      Revision Date: 06/17/2025      SDS Number: 10876233-00015      Date of last issue: 04/14/2025  
Date of first issue: 10/24/2022

### SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Formaldehyde	50-00-0	100	33333

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Respiratory or skin sensitization  
Carcinogenicity

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Formaldehyde	50-00-0	$\geq 0.1 - < 1 \%$
Thiomersal	54-64-8	$< 0.1 \%$

### US State Regulations

#### Pennsylvania Right To Know

Antigen	Not Assigned
Water	7732-18-5
White mineral oil (petroleum)	8042-47-5
Glycerine	56-81-5
Formaldehyde	50-00-0
Thiomersal	54-64-8

#### California Prop. 65

WARNING: This product can expose you to chemicals including Formaldehyde, which is/are known to the State of California to cause cancer, and Thiomersal, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### California List of Hazardous Substances

White mineral oil (petroleum)	8042-47-5
-------------------------------	-----------

#### California Permissible Exposure Limits for Chemical Contaminants

White mineral oil (petroleum)	8042-47-5
Glycerine	56-81-5

#### California Regulated Carcinogens

Formaldehyde	50-00-0
--------------	---------

#### The ingredients of this product are reported in the following inventories:

AICS	: not determined
DSL	: not determined
IECSC	: not determined

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bovilis MH Single Shot RTU / MH + IBR Formulation

Version  
7.0

Revision Date:  
06/17/2025


SDS Number:  
10876233-00015

Date of last issue: 04/14/2025  
Date of first issue: 10/24/2022

### SECTION 16. OTHER INFORMATION

#### Further information

##### NFPA 704:



##### HMIS® IV:

HEALTH	*	2
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA CARC	:	OSHA Specifically Regulated Chemicals/Carcinogens
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA CARC / PEL	:	Permissible exposure limit (PEL)
OSHA CARC / STEL	:	Excursion limit
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bovilis MH Single Shot RTU / MH + IBR Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2025
7.0	06/17/2025	10876233-00015	Date of first issue: 10/24/2022

- International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 06/17/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8