according to the OSHA Hazard Communication Standard



# **Copper Oxide Solid Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 11153924-00010 Date of first issue: 12/20/2022

### **SECTION 1. IDENTIFICATION**

Product name : Copper Oxide Solid Formulation

Other means of identification : COOPERS PERMATRACE COPPER 10 CAPSULES FOR

CALVES AND ADULT CATTLE (47689)

COOPERS PERMATRACE COPPER 20 CAPSULES FOR

CATTLE (47688)

COOPERS PERMATRACE COPPER CAPSULES FOR

ADULT SHEEP & GOATS (47637)

#### Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc Address : 126 E. Lincoln Avenue

Rahway, New Jersey U.S.A. 07065

Telephone : 908-740-4000 Emergency telephone : 1-908-423-6000

E-mail address : EHSDATASTEWARD@merck.com

#### Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product Restrictions on use : Not applicable

#### **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Combustible dust

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

#### Other hazards

Dust contact with the eyes can lead to mechanical irritation. Contact with dust can cause mechanical irritation or drying of the skin.

#### **GHS** label elements

Hazard pictograms



Signal Word : Warning

Hazard Statements : If small particles are generated during further processing, han-

dling or by other means, may form combustible dust concentra-

tions in air.

H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

Precautionary Statements

Prevention:

according to the OSHA Hazard Communication Standard



# **Copper Oxide Solid Formulation**

Version 6.0	Revision Date: 06/17/2025	SDS Number: 11153924-00010	Date of last issue: 04/14/2025 Date of first issue: 12/20/2022		
		P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P280 Wear protective gloves, protective clothing, eye protection and face protection.			
		Response: P308 + P313 IF exposed or concerned: Get medical atte			
<b>Storage:</b> P405 Store locked up.			d up.		
		<b>Disposal:</b> P501 Dispose of odisposal plant.	contents and container to an approved waste		

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

# Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Polyethylene glycol	25322-68-3*	>= 45 - <= 70	TSC
Copper oxide	1317-38-0*	>= 30 - <= 60	TSC
Calcium carbonate	471-34-1*	>= 3 - <= 7	TSC
Diiron trioxide	1309-37-1*	>= 0.5 - <= 1.5	TSC
tert-Butyl-4-methoxyphenol	25013-16-5*	>= 0.1 - <= 1	TSC

<sup>\*</sup> Indicates that the identifier is a CAS No.

### **SECTION 4. FIRST AID MEASURES**

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty

of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : If in eyes, rinse well with water.

Get medical attention if irritation develops and persists.

TSC- the actual concentration or concentration range is withheld as a trade secret

according to the OSHA Hazard Communication Standard



# **Copper Oxide Solid Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 11153924-00010 Date of first issue: 12/20/2022

If swallowed, DO NOT induce vomiting.

Get medical attention.

Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

nd

the skin.

Dust contact with the eyes can lead to mechanical irritation.

Contact with dust can cause mechanical irritation or drying of

Suspected of causing cancer.

Suspected of damaging the unborn child.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

delayed

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Carbon oxides Metal oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for : Sweep up or vacuum up spillage and collect in suitable

according to the OSHA Hazard Communication Standard



# **Copper Oxide Solid Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 11153924-00010 Date of first issue: 12/20/2022

containment and cleaning up container for disposal.

Avoid dispersal of dust in the air (i.e., clearing dust surfaces

with compressed air).

Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

#### **SECTION 7. HANDLING AND STORAGE**

Technical measures : Static electricity may accumulate and ignite suspended dust

causing an explosion.

Provide adequate precautions, such as electrical grounding

and bonding, or inert atmospheres.

Local/Total ventilation Advice on safe handling Use only with adequate ventilation.

Do not breathe dust.

Do not swallow.

Avoid contact with eyes.

Avoid prolonged or repeated contact with skin.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Minimize dust generation and accumulation. Keep container closed when not in use. Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Polyethylene glycol	25322-68-3	TWA (aero-sol)	10 mg/m³	US WEEL
Copper oxide	1317-38-0	TWA (Fumes)	0.1 mg/m³ (Copper)	NIOSH REL
Calcium carbonate	471-34-1	TWA (Respirable)	5 mg/m³ (Calcium car- bonate)	NIOSH REL

according to the OSHA Hazard Communication Standard



# **Copper Oxide Solid Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 06/17/2025 11153924-00010 Date of first issue: 12/20/2022 6.0

		TWA (total)	10 mg/m³ (Calcium car- bonate)	NIOSH REL
Diiron trioxide	1309-37-1	TWA (Res- pirable par- ticulate mat- ter)	5 mg/m³	ACGIH
		TWA (dust and fume)	5 mg/m³ (Iron)	NIOSH REL
		TWA (Fumes)	10 mg/m <sup>3</sup>	OSHA Z-1
		TWA (total dust)	15 mg/m³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m³	OSHA Z-1

**Engineering measures** Use feasible engineering controls to minimize exposure to

compound.

All engineering controls should be implemented by facility design and operated in accordance with GMP principles to

protect products, workers, and the environment.

Personal protective equipment

Respiratory protection General and local exhaust ventilation is recommended to

> maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are

> unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any

hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material Chemical-resistant gloves

Eye protection Wear safety glasses with side shields or goggles.

If the work environment or activity involves dusty conditions,

mists or aerosols, wear the appropriate goggles.

Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or

aerosols.

Skin and body protection

Work uniform or laboratory coat. Hygiene measures

If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures,

according to the OSHA Hazard Communication Standard



# **Copper Oxide Solid Formulation**

Version 6.0

Revision Date: 06/17/2025

SDS Number: 11153924-00010

Date of last issue: 04/14/2025 Date of first issue: 12/20/2022

industrial hygiene monitoring, medical surveillance and the

use of administrative controls.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES** 

Appearance : capsule

Color : metallic

gray

Odor : No data available

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : May form explosive dust-air mixture during processing,

handling or other means.

Flammability (liquids) : Not applicable

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : No data available

Density : No data available

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

: Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

according to the OSHA Hazard Communication Standard



# **Copper Oxide Solid Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 11153924-00010 Date of first issue: 12/20/2022

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle characteristics

Particle size : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard. Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

May form explosive dust-air mixture during processing,

handling or other means.

Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Avoid dust formation.
Oxidizing agents

Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

### **Acute toxicity**

Not classified based on available information.

### **Components:**

### Polyethylene glycol:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 423

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Remarks: Based on data from similar materials

Copper oxide:

Acute oral toxicity : LD50 (Rat): > 2,500 mg/kg

Assessment: The substance or mixture has no acute oral tox-

according to the OSHA Hazard Communication Standard



# **Copper Oxide Solid Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 11153924-00010 Date of first issue: 12/20/2022

icity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Calcium carbonate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 420

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Diiron trioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : LC50 (Rat): > 5.05 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

tert-Butyl-4-methoxyphenol:

Acute oral toxicity : LD50 (Rabbit): 2,100 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Not classified based on available information.

**Components:** 

Polyethylene glycol:

Species : Rabbit

according to the OSHA Hazard Communication Standard



# **Copper Oxide Solid Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 11153924-00010 Date of first issue: 12/20/2022

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Copper oxide:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Calcium carbonate:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Diiron trioxide:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

tert-Butyl-4-methoxyphenol:

Species : Rabbit Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

**Components:** 

Polyethylene glycol:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Copper oxide:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Calcium carbonate:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Diiron trioxide:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

according to the OSHA Hazard Communication Standard



# **Copper Oxide Solid Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 11153924-00010 Date of first issue: 12/20/2022

#### tert-Butyl-4-methoxyphenol:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days Remarks : Based on data from similar materials

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

### Respiratory sensitization

Not classified based on available information.

#### **Components:**

### Polyethylene glycol:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Remarks : Based on data from similar materials

### Copper oxide:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

#### Calcium carbonate:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

#### tert-Butyl-4-methoxyphenol:

Test Type : Human repeat insult patch test (HRIPT)

Routes of exposure : Skin contact Result : negative

### Germ cell mutagenicity

Not classified based on available information.

#### Components:

### Polyethylene glycol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

according to the OSHA Hazard Communication Standard



# **Copper Oxide Solid Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 11153924-00010 Date of first issue: 12/20/2022

П

Copper oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Calcium carbonate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Diiron trioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: In vivo mammalian alkaline comet assay

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 489

Result: negative

tert-Butyl-4-methoxyphenol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

Result: negative

according to the OSHA Hazard Communication Standard



# **Copper Oxide Solid Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 11153924-00010 Date of first issue: 12/20/2022

П

Carcinogenicity

Suspected of causing cancer.

**Components:** 

tert-Butyl-4-methoxyphenol:

Species: RatApplication Route: IngestionExposure time: 104 weeksResult: positive

Species : Hamster, male
Application Route : Ingestion
Exposure time : 24 weeks
Result : positive

Carcinogenicity - Assess- : Limited evidence of carcinogenicity in animal studies

ment

**IARC** Group 2B: Possibly carcinogenic to humans

tert-Butyl-4-methoxyphenol 25013-16-5

(butylated hydroxyanisole)

(BHA)

**OSHA**No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP Reasonably anticipated to be a human carcinogen

tert-Butyl-4-methoxyphenol 25013-16-5

(Butylated Hydroxyanisole)

(BHA)

Reproductive toxicity

Suspected of damaging the unborn child.

**Components:** 

Copper oxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Remarks: Based on data from similar materials

Calcium carbonate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

according to the OSHA Hazard Communication Standard



# **Copper Oxide Solid Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 11153924-00010 Date of first issue: 12/20/2022

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

tert-Butyl-4-methoxyphenol:

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Fertility/early embryonic development

Species: Mouse

Application Route: Ingestion

Result: positive

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on development, based on

animal experiments.

### STOT-single exposure

Not classified based on available information.

### STOT-repeated exposure

Not classified based on available information.

### Repeated dose toxicity

### **Components:**

### Copper oxide:

Species : Mouse
NOAEL : 1000 ppm
Application Route : Ingestion
Exposure time : 92 Days

Remarks : Based on data from similar materials

#### Calcium carbonate:

Species : Rat

NOAEL : > 1,000 mg/kg
Application Route : Ingestion
Exposure time : 28 Days

Method : OECD Test Guideline 422

### Diiron trioxide:

Species : Rat

NOAEL : >= 1,000 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Method : OECD Test Guideline 408

according to the OSHA Hazard Communication Standard



# **Copper Oxide Solid Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 06/17/2025 11153924-00010 Date of first issue: 12/20/2022 6.0

### tert-Butyl-4-methoxyphenol:

Species Rat NOAEL : 50 mg/kg : 250 mg/kg LOAEL Application Route : Ingestion Exposure time 8 Months

### **Aspiration toxicity**

Not classified based on available information.

### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

### **Components:**

Polyethylene glycol:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Copper oxide:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): > 0.01 - 0.1

mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 0.1 - 1 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

icity)

Toxicity to fish (Chronic tox- : NOEC (Oncorhynchus mykiss (rainbow trout)): > 0.001 - 0.01

Exposure time: 32 d

Remarks: Based on data from similar materials

aquatic invertebrates (Chron-

ic toxicity)

Toxicity to daphnia and other : NOEC (Ceriodaphnia dubia (water flea)): > 0.001 - 0.01 mg/l

Exposure time: 7 d

Remarks: Based on data from similar materials

### Calcium carbonate:

LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Toxicity to fish

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Toxicity to daphnia and other:

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

according to the OSHA Hazard Communication Standard



# Copper Oxide Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 06/17/2025 11153924-00010 Date of first issue: 12/20/2022 6.0

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Toxicity to algae/aquatic NOELR (Pseudokirchneriella subcapitata (green algae)): 50

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

EL50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

NOEC: 1,000 mg/l Toxicity to microorganisms

Exposure time: 3 h

Method: OECD Test Guideline 209

EC50: > 1,000 mg/lExposure time: 3 h

Method: OECD Test Guideline 209

Diiron trioxide:

plants

Toxicity to fish LL50 (Danio rerio (zebra fish)): > 10,000 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Raphidocelis subcapitata (freshwater green alga)): > 20

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOELR (Raphidocelis subcapitata (freshwater green alga)):

>= 20 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other:

aquatic invertebrates (Chron-

ic toxicity)

NOELR (Daphnia magna (Water flea)): >= 20 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Toxicity to microorganisms EL50 (activated sludge): >= 100 mg/l

> Exposure time: 3 h Method: ISO 8192

Remarks: Based on data from similar materials

tert-Butyl-4-methoxyphenol:

Toxicity to fish LC50 (Danio rerio (zebra fish)): 1.56 mg/l

according to the OSHA Hazard Communication Standard



# **Copper Oxide Solid Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 11153924-00010 Date of first issue: 12/20/2022

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 2.3 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): 1.9

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.25

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

### Persistence and degradability

### **Components:**

Polyethylene glycol:

Biodegradability : Result: rapidly degradable

Remarks: Based on data from similar materials

### **Bioaccumulative potential**

#### **Components:**

### Polyethylene glycol:

Partition coefficient: n-

octanol/water

: log Pow: < 3

#### tert-Butyl-4-methoxyphenol:

Bioaccumulation : Species: Oryzias latipes (Orange-red killifish)

Bioconcentration factor (BCF): 16 - 21

Partition coefficient: n-

octanol/water

: log Pow: 2.82

Method: OECD Test Guideline 117

# Mobility in soil

No data available

#### Other adverse effects

No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

#### **Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste

according to the OSHA Hazard Communication Standard



# **Copper Oxide Solid Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 11153924-00010 Date of first issue: 12/20/2022

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

#### **SECTION 14. TRANSPORT INFORMATION**

### **International Regulations**

**UNRTDG** 

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Copper oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

**IATA-DGR** 

UN/ID No. : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Copper oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo : 956

aircraft)

Packing instruction (passen: 956

ger aircraft)

Environmentally hazardous : yes

**IMDG-Code** 

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Copper oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

**Domestic regulation** 

**49 CFR** 

UN/ID/NA number : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Copper oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171

Marine pollutant : yes(Copper oxide, 2,6-Di-tert-butyl-p-cresol)

Remarks : Above applies only to containers over 119 gallons or 450

according to the OSHA Hazard Communication Standard



# **Copper Oxide Solid Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 11153924-00010 Date of first issue: 12/20/2022

liters.

Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO. Above applies only to containers over 119 gallons or 450 liters.

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Combustible dust

Carcinogenicity
Reproductive toxicity

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Copper oxide 1317-38-0 >= 30 - < 50 %

### **US State Regulations**

### Pennsylvania Right To Know

Polyethylene glycol 25322-68-3
Copper oxide 1317-38-0
Polyethylene Oxide 25372-68-3
Calcium carbonate 471-34-1
Diiron trioxide 1309-37-1

#### California Prop. 65

WARNING: This product can expose you to chemicals including tert-Butyl-4-methoxyphenol, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

#### **California List of Hazardous Substances**

Copper oxide 1317-38-0 Diiron trioxide 1309-37-1

# California Permissible Exposure Limits for Chemical Contaminants

Calcium carbonate 471-34-1 Diiron trioxide 1309-37-1

according to the OSHA Hazard Communication Standard



# **Copper Oxide Solid Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 11153924-00010 Date of first issue: 12/20/2022

#### The ingredients of this product are reported in the following inventories:

AICS : not determined


DSL : not determined

IECSC : not determined

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA 704:



Special hazard

#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA Z-1 / TWA : 8-hour time weighted average

US WEEL / TWA : 8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized Sys-

according to the OSHA Hazard Communication Standard



# **Copper Oxide Solid Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/17/2025 11153924-00010 Date of first issue: 12/20/2022

tem; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NTP - National Toxicology Program: NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 06/17/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8