according to the OSHA Hazard Communication Standard



Cefquinome LC Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11384007-00005 Date of first issue: 04/29/2024

SECTION 1. IDENTIFICATION

Product name : Cefquinome LC Formulation Other means of identification : Cobactan LC (A008116)

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc Address : 126 E. Lincoln Avenue

Rahway, New Jersey U.S.A. 07065

Telephone : 908-740-4000 Emergency telephone : 1-908-423-6000

E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Aspiration hazard : Category 1

Other hazards

None known.

GHS label elements

Hazard pictograms



Signal Word : Danger

Hazard Statements : H304 May be fatal if swallowed and enters airways.

Precautionary Statements : Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER.

P331 Do NOT induce vomiting.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

according to the OSHA Hazard Communication Standard



Cefquinome LC Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11384007-00005 Date of first issue: 04/29/2024

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Paraffin oil	8012-95-1*	>= 60 - <= 80	TSC
Petrolatum	8009-03-8*	>= 10 - <= 30	TSC
Cefquinome	118443-89-3*	>= 0.5 - <= 1.5	TSC

^{*} Indicates that the identifier is a CAS No.

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention if symptoms occur.

Clush associate materials and a properties.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.

If vomiting occurs have person lean forward.

Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

May be fatal if swallowed and enters airways.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod- : Carbon oxides

TSC- the actual concentration or concentration range is withheld as a trade secret

according to the OSHA Hazard Communication Standard



Cefquinome LC Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11384007-00005 Date of first issue: 04/29/2024

ucts

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions

Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation

Use only with adequate ventilation.

Advice on safe handling

Avoid inhalation of vapor or mist.

Do not swallow.

Avoid contact with eyes.

Avoid prolonged or repeated contact with skin.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

according to the OSHA Hazard Communication Standard



Cefquinome LC Formulation

Version **Revision Date:** SDS Number: Date of last issue: 04/14/2025 06/18/2025 11384007-00005 Date of first issue: 04/29/2024 4.0

assessment

Keep container tightly closed.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage Keep in properly labeled containers.

> Store locked up. Keep tightly closed.

Store in accordance with the particular national regulations.

Materials to avoid Do not store with the following product types:

Strong oxidizing agents

Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis	
Paraffin oil	8012-95-1	TWA (Mist)	5 mg/m³	OSHA Z-1	
		TWA (Inhal-	5 mg/m ³	ACGIH	
		able particu-			
		late matter)			
		TWA (Mist)	5 mg/m³	NIOSH REL	
		ST (Mist)	10 mg/m ³	NIOSH REL	
Petrolatum	8009-03-8	TWA (Mist)	5 mg/m³	OSHA Z-1	
		TWA (Inhal-	5 mg/m³	ACGIH	
		able particu-			
		late matter)			
		TWA (Mist)	5 mg/m³	NIOSH REL	
		ST (Mist)	10 mg/m ³	NIOSH REL	
Cefquinome	118443-89-3	TWA	2000 μg/m3 (OEB 1)	Internal	
	Further information: RSEN				

Engineering measures

Use appropriate engineering controls and manufacturing technologies to control airborne concentrations (e.g., drip-

less quick connections).

All engineering controls should be implemented by facility design and operated in accordance with GMP principles to

protect products, workers, and the environment.

Laboratory operations do not require special containment.

Personal protective equipment

Respiratory protection General and local exhaust ventilation is recommended to

> maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn.

Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air

according to the OSHA Hazard Communication Standard



Cefquinome LC Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11384007-00005 Date of first issue: 04/29/2024

supplied respirator if there is any potential for uncontrolled

release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : Chemical-resistant gloves

Eye protection : Wear safety glasses with side shields or goggles.

If the work environment or activity involves dusty conditions,

mists or aerosols, wear the appropriate goggles.

Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or

aerosols.

Skin and body protection Hygiene measures Work uniform or laboratory coat.

: If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the

use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : ointment

Color : White to light yellow

Odor : No data available

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower : No data available

according to the OSHA Hazard Communication Standard



Cefquinome LC Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11384007-00005 Date of first issue: 04/29/2024

flammability limit

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : No data available

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle characteristics

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.
Chemical stability : Stable under normal conditions.

Possibility of hazardous reac- :

tions

Can react with strong oxidizing agents.

Conditions to avoid : None known. Incompatible materials : Oxidizing agents

Hazardous decomposition : No hazardous decomposition products are known.

products

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

according to the OSHA Hazard Communication Standard



Cefquinome LC Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11384007-00005 Date of first issue: 04/29/2024

Acute toxicity

Not classified based on available information.

Components:

Paraffin oil:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Petrolatum:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Cefquinome:

Acute oral toxicity : LD50 (Mouse): > 5,000 mg/kg

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Skin corrosion/irritation

Not classified based on available information.

Components:

Paraffin oil:

Species : Rabbit

Result : No skin irritation

Petrolatum:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Cefquinome:

Result : Irritating to skin.

Serious eye damage/eye irritation

Not classified based on available information.

according to the OSHA Hazard Communication Standard



Cefquinome LC Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11384007-00005 Date of first issue: 04/29/2024

Components:

Paraffin oil:

Species : Rabbit

Result : No eye irritation

Petrolatum:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Cefquinome:

Result : Irritating to eyes.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Petrolatum:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Remarks : Based on data from similar materials

Cefquinome:

Routes of exposure : Inhalation

Result : May cause sensitization by inhalation.

Germ cell mutagenicity

Not classified based on available information.

Components:

Petrolatum:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

according to the OSHA Hazard Communication Standard



Cefquinome LC Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11384007-00005 Date of first issue: 04/29/2024

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Petrolatum:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Petrolatum:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Skin contact

Result: negative

Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

Components:

Cefquinome:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

according to the OSHA Hazard Communication Standard



Cefquinome LC Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11384007-00005 Date of first issue: 04/29/2024

Repeated dose toxicity

Components:

Paraffin oil:

Species : Rat, female
LOAEL : 161 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Petrolatum:

Species : Rat

NOAEL : 5,000 mg/kg
Application Route : Ingestion
Exposure time : 2 y

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Paraffin oil:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Experience with human exposure

Components:

Cefquinome:

Inhalation : Symptoms: anaphylaxis, bronchospasm, Cough, respiratory

tract irritation, Rash, rhinitis, runny nose, sneezing

Remarks: May produce an allergic reaction.

Skin contact : Remarks: May irritate skin.

May produce an allergic reaction.

Eye contact : Remarks: May irritate eyes.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Paraffin oil:

Toxicity to fish : LL50 (Scophthalmus maximus (turbot)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Acartia tonsa (Calanoid copepod)): > 100 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

according to the OSHA Hazard Communication Standard



Cefquinome LC Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11384007-00005 Date of first issue: 04/29/2024

Remarks: Based on data from similar materials

Toxicity to algae/aquatic : EL50 (Skeletonema costatum (marine diatom)): > 100 mg/l

plants Exposure time: 72 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

NOELR (Skeletonema costatum (marine diatom)): > 1 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Petrolatum:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

NOEL (Pseudokirchneriella subcapitata (green algae)): >=

100 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 10 mg/l

Exposure time: 21 d

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Cefquinome:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 500 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 86 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 37

ng/l

Exposure time: 72 h

according to the OSHA Hazard Communication Standard



Cefquinome LC Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11384007-00005 Date of first issue: 04/29/2024

Method: OECD Test Guideline 201

EC50 (Anabaena flos-aquae (cyanobacterium)): 0.041 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Anabaena flos-aquae (cyanobacterium)): 0.014 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,000 mg/l

Exposure time: 3 h

Test Type: Respiration inhibition Method: OECD Test Guideline 209

NOEC: 295.3 mg/l Exposure time: 3 h

Test Type: Respiration inhibition Method: OECD Test Guideline 209

Persistence and degradability

Components:

Petrolatum:

Biodegradability : Result: Not readily biodegradable.

Method: OECD Test Guideline 301F

Remarks: The test was conducted according to guideline

Based on data from similar materials

Cefquinome:

Biodegradability : Result: not rapidly degradable

Biodegradation: 40 % Exposure time: 30 d

Method: OECD Test Guideline 302B

Stability in water : Hydrolysis: > 90 %(5 d)

Method: FDA 3.09

Bioaccumulative potential

Components:

Paraffin oil:

Partition coefficient: n- : log Pow: > 4

octanol/water Remarks: Calculation

Cefquinome:

Partition coefficient: n-

octanol/water

log Pow: -2.01

according to the OSHA Hazard Communication Standard



Cefquinome LC Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11384007-00005 Date of first issue: 04/29/2024

Mobility in soil

Components:

Cefquinome:

Distribution among environ: log Koc: 2.76

mental compartments

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Aspiration hazard

according to the OSHA Hazard Communication Standard



Cefquinome LC Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11384007-00005 Date of first issue: 04/29/2024

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Paraffin oil 8012-95-1 Petrolatum 8009-03-8

California List of Hazardous Substances

Paraffin oil 8012-95-1 Petrolatum 8009-03-8

California Permissible Exposure Limits for Chemical Contaminants

Paraffin oil 8012-95-1 Petrolatum 8009-03-8

The ingredients of this product are reported in the following inventories:

AICS : not determined


DSL : not determined

IECSC : not determined

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

according to the OSHA Hazard Communication Standard



Cefquinome LC Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11384007-00005 Date of first issue: 04/29/2024

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 06/18/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

according to the OSHA Hazard Communication Standard



Cefquinome LC Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11384007-00005 Date of first issue: 04/29/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8