according to the OSHA Hazard Communication Standard



Aluminum Chloride (with Bentonite) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/18/2025 11496198-00006 Date of first issue: 12/23/2024

SECTION 1. IDENTIFICATION

Product name : Aluminum Chloride (with Bentonite) Formulation

Product code : Proquatic PondFlocc

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc Address : 126 E. Lincoln Avenue

Rahway, New Jersey U.S.A. 07065

Telephone : 908-740-4000 Emergency telephone : 1-908-423-6000

E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Combustible dust

Serious eye damage : Category 1

Other hazards

Contact with dust can cause mechanical irritation or drying of the skin.

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : If small particles are generated during further processing, han-

dling or by other means, may form combustible dust concentra-

tions in air.

H318 Causes serious eye damage.

Supplemental Hazard State-

ments

Corrosive to the respiratory tract.

Precautionary Statements : Prevention:

P280 Wear eye protection and face protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with

according to the OSHA Hazard Communication Standard



Aluminum Chloride (with Bentonite) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/18/2025 11496198-00006 Date of first issue: 12/23/2024

water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Aluminum chloride, basic	1327-41-9*	>= 65 - <= 85	TSC
Bentonite	1302-78-9*	>= 10 - <= 30	TSC

^{*} Indicates that the identifier is a CAS No.

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap.

Get medical attention if symptoms occur.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention immediately.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Contact with dust can cause mechanical irritation or drying of

Most important symptoms and effects, both acute and

and the skin.

delayed

Causes serious eye damage.

Corrosive to the respiratory tract.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

TSC- the actual concentration or concentration range is withheld as a trade secret

according to the OSHA Hazard Communication Standard



Aluminum Chloride (with Bentonite) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/18/2025 11496198-00006 Date of first issue: 12/23/2024

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Avoid generating dust; fine dust dispersed in air in sufficient

concentrations, and in the presence of an ignition source is a

potential dust explosion hazard.

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Metal oxides

Chlorine compounds

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

Avoid dispersal of dust in the air (i.e., clearing dust surfaces

with compressed air).

Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

according to the OSHA Hazard Communication Standard



Aluminum Chloride (with Bentonite) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/18/2025 11496198-00006 Date of first issue: 12/23/2024

Technical measures : Static electricity may accumulate and ignite suspended dust

causing an explosion.

Provide adequate precautions, such as electrical grounding

and bonding, or inert atmospheres. Use only with adequate ventilation.

Local/Total ventilation :

Advice on safe handling : Do not breathe dust.

Do not swallow. Do not get in eyes.

Avoid prolonged or repeated contact with skin.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Keep container tightly closed.

Minimize dust generation and accumulation. Keep container closed when not in use. Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Keep tightly closed.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

inert or nuisance dust 50 Million particles per cubic foot

Value type (Form of exposure): TWA (total dust)

Basis: OSHA Z-3

15 mg/m³

Value type (Form of exposure): TWA (total dust)

Basis: OSHA Z-3

5 mg/m³

Value type (Form of exposure): TWA (respirable fraction)

Basis: OSHA Z-3

15 Million particles per cubic foot

Value type (Form of exposure): TWA (respirable fraction)

Basis: OSHA Z-3

Dust, nuisance dust and par-

ticulates

10 mg/m³

Value type (Form of exposure): PEL (Total dust)

Basis: CAL PEL

5 mg/m³

Value type (Form of exposure): PEL (respirable dust fraction)

Basis: CAL PEL

according to the OSHA Hazard Communication Standard



Aluminum Chloride (with Bentonite) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/18/2025 11496198-00006 Date of first issue: 12/23/2024

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Aluminum chloride, basic	1327-41-9	TWA	2 mg/m³ (Aluminum)	NIOSH REL

Engineering measures : All eng

All engineering controls should be implemented by facility design and operated in accordance with GMP principles to

protect products, workers, and the environment.

Containment technologies suitable for controlling compounds are required to control at source and to prevent migration of the compound to uncontrolled areas (e.g., open-face

containment devices). Minimize open handling.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any

hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Consider double gloving.

Eye protection : Wear safety glasses with side shields or goggles.

If the work environment or activity involves dusty conditions.

mists or aerosols, wear the appropriate goggles.

Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or

aerosols.

Skin and body protection : Work uniform or laboratory coat.

Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces.

Use appropriate degowning techniques to remove potentially

contaminated clothing.

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

The effective operation of a facility should include review of

according to the OSHA Hazard Communication Standard



Aluminum Chloride (with Bentonite) Formulation

Version 6.0 Revision Date: 06/18/2025

SDS Number: 11496198-00006

Date of last issue: 04/14/2025 Date of first issue: 12/23/2024

engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Color : yellow

Odor : characteristic

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : May form explosive dust-air mixture during processing,

handling or other means.

Flammability (liquids) : Not applicable

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : Not applicable

Relative density : No data available

Density : No data available

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

: Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

according to the OSHA Hazard Communication Standard



Aluminum Chloride (with Bentonite) Formulation

Version Revision Date: Date of last issue: 04/14/2025 SDS Number: 06/18/2025 11496198-00006 Date of first issue: 12/23/2024 6.0

Viscosity

Viscosity, kinematic Not applicable

Explosive properties Not explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

Molecular weight No data available

Particle characteristics

Particle size No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity Not classified as a reactivity hazard. Chemical stability Stable under normal conditions.

Possibility of hazardous reac-

tions

May form explosive dust-air mixture during processing,

handling or other means.

Can react with strong oxidizing agents.

Conditions to avoid Heat, flames and sparks.

Avoid dust formation.

Incompatible materials

Oxidizing agents Hazardous decomposition

products

: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

Aluminum chloride, basic:

Acute oral toxicity LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral tox-

icity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Bentonite:

according to the OSHA Hazard Communication Standard



Aluminum Chloride (with Bentonite) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/18/2025 11496198-00006 Date of first issue: 12/23/2024

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 425

Acute inhalation toxicity : LC50 (Rat): > 5.27 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 436

Skin corrosion/irritation

Not classified based on available information.

Components:

Aluminum chloride, basic:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Bentonite:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Aluminum chloride, basic:

Species : Rabbit

Result : Irreversible effects on the eye Method : OECD Test Guideline 405

Bentonite:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

according to the OSHA Hazard Communication Standard



Aluminum Chloride (with Bentonite) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/18/2025 11496198-00006 Date of first issue: 12/23/2024

Components:

Aluminum chloride, basic:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact
Species : Mouse
Result : negative

Bentonite:

Routes of exposure : Skin contact Species : Mouse Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Aluminum chloride, basic:

Genotoxicity in vitro : Test Type: in vitro micronucleus test

Method: OECD Test Guideline 487

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay)

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Bentonite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

according to the OSHA Hazard Communication Standard



Aluminum Chloride (with Bentonite) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/18/2025 11496198-00006 Date of first issue: 12/23/2024

Carcinogenicity

Not classified based on available information.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Aluminum chloride, basic:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Bentonite:

Effects on fertility : Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

STOT-single exposure

Corrosive to the respiratory tract.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Aluminum chloride, basic:

Species : Rat

NOAEL : 200 mg/kg LOAEL : 1,000 mg/kg

according to the OSHA Hazard Communication Standard



Aluminum Chloride (with Bentonite) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 06/18/2025 11496198-00006 Date of first issue: 12/23/2024 6.0

Application Route : Ingestion Exposure time : 28 - 53 Days

Method : OECD Test Guideline 422

Bentonite:

Species Mouse NOAEL : 500 mg/kg Application Route : Ingestion Exposure time : 90 Days

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Aluminum chloride, basic:

Toxicity to fish LC50 (Danio rerio (zebra fish)): > 1 - 10 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 1 -

plants 10 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Ecotoxicology Assessment

Chronic aquatic toxicity No toxicity at the limit of solubility.

Bentonite:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 16,000 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: ErC50: > 100 mg/l

Exposure time: 72 h

according to the OSHA Hazard Communication Standard



Aluminum Chloride (with Bentonite) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 06/18/2025 11496198-00006 Date of first issue: 12/23/2024 6.0

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Empty containers should be taken to an approved waste Contaminated packaging

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number UN 3260

Proper shipping name CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S.

(Aluminum chloride, basic)

Class 8 Ш Packing group 8 Labels Environmentally hazardous nο

IATA-DGR

UN/ID No. UN 3260

Proper shipping name Corrosive solid, acidic, inorganic, n.o.s.

(Aluminum chloride, basic)

Class 8 Ш Packing group Labels Corrosive Packing instruction (cargo 864

aircraft)

Packing instruction (passen-860

ger aircraft)

IMDG-Code

UN number UN 3260

Proper shipping name CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S.

(Aluminum chloride, basic)

Class 8 Packing group Ш Labels 8

according to the OSHA Hazard Communication Standard



Aluminum Chloride (with Bentonite) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/18/2025 11496198-00006 Date of first issue: 12/23/2024

EmS Code : F-A, S-B Marine pollutant : no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 3260

Proper shipping name : Corrosive solid, acidic, inorganic, n.o.s.

(Aluminum chloride, basic)

Class : 8 Packing group : III

Labels : CORROSIVE

ERG Code : 154 Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Combustible dust

Serious eye damage or eye irritation

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Aluminum chloride, basic 1327-41-9
Bentonite 1302-78-9

California List of Hazardous Substances

Aluminum chloride, basic 1327-41-9

California Permissible Exposure Limits for Chemical Contaminants

Aluminum chloride, basic 1327-41-9

according to the OSHA Hazard Communication Standard



Aluminum Chloride (with Bentonite) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/18/2025 11496198-00006 Date of first issue: 12/23/2024

The ingredients of this product are reported in the following inventories:

AICS : not determined

DSL : not determined

IECSC : not determined

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:

Health 3 0 Instability

Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

CAL PEL : California permissible exposure limits for chemical contami-

nants (Title 8, Article 107)

NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

CAL PEL / PEL : Permissible exposure limit

NIOSH REL / TWA Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized Sys-

according to the OSHA Hazard Communication Standard



Aluminum Chloride (with Bentonite) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 6.0 06/18/2025 11496198-00006 Date of first issue: 12/23/2024

tem; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods: IMO - International Maritime Organization: ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization: KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods, vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 06/18/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8