

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate (with Mineral Oil) Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
5.2	09/28/2024	5060473-00013	Date of first issue: 10/17/2019

SECTION 1. IDENTIFICATION

Product name : Bismuth Subnitrate (with Mineral Oil) Formulation
Other means of identification : Shutout (A011866)
CEPRALOCK (89964)

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc
Address : 126 E. Lincoln Avenue
Rahway, New Jersey U.S.A. 07065
Telephone : 908-740-4000
Emergency telephone : 1-908-423-6000
E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Specific target organ toxicity : Category 1 (Central nervous system)
- repeated exposure

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P260 Do not breathe dust, fume, gas, mist, vapors or spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
Response:
P314 Get medical attention if you feel unwell.
Disposal:
P501 Dispose of contents and container to an approved waste disposal plant.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version 5.2 Revision Date: 09/28/2024 SDS Number: 5060473-00013 Date of last issue: 12/06/2023
Date of first issue: 10/17/2019

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Bismuth hydroxide nitrate oxide	1304-85-4	65
White mineral oil (petroleum)	8042-47-5	29.4
Fatty acids, C14-26, aluminum salts	97404-28-9	4.8

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : Causes damage to organs through prolonged or repeated exposure.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Nitrogen oxides (NO_x)
Metal oxides

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
5.2	09/28/2024	5060473-00013	Date of first issue: 10/17/2019

Carbon oxides

- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not breathe dust, fume, gas, mist, vapors or spray.
Do not swallow.
Avoid contact with eyes.
Avoid prolonged or repeated contact with skin.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version 5.2 Revision Date: 09/28/2024 SDS Number: 5060473-00013 Date of last issue: 12/06/2023
Date of first issue: 10/17/2019

Materials to avoid : Store in accordance with the particular national regulations.
: Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Explosives
Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Fatty acids, C14-26, aluminum salts	97404-28-9	TWA (Respirable particulate matter)	1 mg/m ³ (Aluminum)	ACGIH

Engineering measures : Use feasible engineering controls to minimize exposure to compound.
All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection
Material : Chemical-resistant gloves

Eye protection : Wear safety glasses with side shields or goggles.
If the work environment or activity involves dusty conditions, mists or aerosols, wear the appropriate goggles.
Wear a faceshield or other full face protection if there is a

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
5.2	09/28/2024	5060473-00013	Date of first issue: 10/17/2019

Skin and body protection	:	potential for direct contact to the face with dusts, mists, or aerosols.
Hygiene measures	:	Work uniform or laboratory coat. If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use. The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	ointment
Color	:	White to light yellow
Odor	:	No data available
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	No data available
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Relative density	:	No data available
Density	:	No data available
Solubility(ies) Water solubility	:	No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
5.2	09/28/2024	5060473-00013	Date of first issue: 10/17/2019

Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available
Particle characteristics	:	
Particle size	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	None known.
Conditions to avoid	:	None known.
Incompatible materials	:	None.
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Acute oral toxicity	:	LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 423 Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): > 5.07 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 436

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
5.2	09/28/2024	5060473-00013	Date of first issue: 10/17/2019

Remarks: Based on data from similar materials

White mineral oil (petroleum):

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity

Fatty acids, C14-26, aluminum salts:

Acute oral toxicity	:	LD50 (Rat, female): > 2,000 mg/kg Method: OECD Test Guideline 423 Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): > 5.15 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Species	:	reconstructed human epidermis (RhE)
Method	:	OECD Test Guideline 439
Result	:	No skin irritation

White mineral oil (petroleum):

Species	:	Rabbit
Result	:	No skin irritation

Fatty acids, C14-26, aluminum salts:

Species	:	reconstructed human epidermis (RhE)
Method	:	OECD Test Guideline 431
Remarks	:	Based on data from similar materials
Species	:	reconstructed human epidermis (RhE)
Method	:	OECD Test Guideline 439
Remarks	:	Based on data from similar materials

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
5.2	09/28/2024	5060473-00013	Date of first issue: 10/17/2019

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405

White mineral oil (petroleum):

Species	: Rabbit
Result	: No eye irritation

Fatty acids, C14-26, aluminum salts:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405
Remarks	: Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative

White mineral oil (petroleum):

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: negative

Fatty acids, C14-26, aluminum salts:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
5.2	09/28/2024	5060473-00013	Date of first issue: 10/17/2019

Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	negative
Remarks	:	Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative Remarks: Based on data from similar materials
-----------------------	---	---

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

White mineral oil (petroleum):

Genotoxicity in vitro	:	Test Type: In vitro mammalian cell gene mutation test Result: negative
-----------------------	---	---

Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: negative Remarks: Based on data from similar materials
----------------------	---	--

Fatty acids, C14-26, aluminum salts:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative Remarks: Based on data from similar materials
-----------------------	---	--

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
5.2	09/28/2024	5060473-00013	Date of first issue: 10/17/2019

Components:

White mineral oil (petroleum):

Species	:	Rat
Application Route	:	Ingestion
Exposure time	:	24 Months
Result	:	negative

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Effects on fertility	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
		Species: Rat
		Application Route: Ingestion
		Result: negative

Effects on fetal development	:	Test Type: Embryo-fetal development
		Species: Rat
		Application Route: Ingestion
		Method: OECD Test Guideline 414
		Result: negative

White mineral oil (petroleum):

Effects on fertility	:	Test Type: One-generation reproduction toxicity study
		Species: Rat
		Application Route: Skin contact
		Result: negative

Effects on fetal development	:	Test Type: Embryo-fetal development
		Species: Rat
		Application Route: Ingestion
		Result: negative

Fatty acids, C14-26, aluminum salts:

Effects on fertility	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
		Species: Rat
		Application Route: Ingestion

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
5.2	09/28/2024	5060473-00013	Date of first issue: 10/17/2019

Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Components:

Bismuth hydroxide nitrate oxide:

Target Organs	: Central nervous system
Assessment	: Causes damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

White mineral oil (petroleum):

Species	: Rat
LOAEL	: 160 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days
Species	: Rat
LOAEL	: >= 1 mg/l
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 4 Weeks
Method	: OECD Test Guideline 412

Fatty acids, C14-26, aluminum salts:

Species	: Rat
	: >= 1000 mg/kg
Application Route	: Ingestion
Exposure time	: 42 Days
Remarks	: Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
5.2	09/28/2024	5060473-00013	Date of first issue: 10/17/2019

Experience with human exposure

Components:

Bismuth hydroxide nitrate oxide:

Ingestion : Target Organs: Blood
Symptoms: Methaemoglobinemia
Target Organs: Central nervous system
Symptoms: Neurological disorders

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Bismuth hydroxide nitrate oxide:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 137 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 137 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 137 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): > 137 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

White mineral oil (petroleum):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
5.2	09/28/2024	5060473-00013	Date of first issue: 10/17/2019

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l
Exposure time: 28 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1,000 mg/l
Exposure time: 21 d

Persistence and degradability

Components:

White mineral oil (petroleum):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d

Fatty acids, C14-26, aluminum salts:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 81.2 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
Remarks: Based on data from similar materials

Bioaccumulative potential

Components:

Fatty acids, C14-26, aluminum salts:

Partition coefficient: n-octanol/water : log Pow: > 7
Remarks: Calculation

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.
Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
5.2	09/28/2024	5060473-00013	Date of first issue: 10/17/2019

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Specific target organ toxicity (single or repeated exposure)

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Bismuth hydroxide nitrate oxide	1304-85-4
White mineral oil (petroleum)	8042-47-5
Fatty acids, C14-26, aluminum salts	97404-28-9

California List of Hazardous Substances

White mineral oil (petroleum)	8042-47-5
-------------------------------	-----------

California Permissible Exposure Limits for Chemical Contaminants

White mineral oil (petroleum)	8042-47-5
-------------------------------	-----------

The ingredients of this product are reported in the following inventories:

AICS : not determined

DSL : not determined

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate (with Mineral Oil) Formula-tion


Version 5.2 Revision Date: 09/28/2024 SDS Number: 5060473-00013 Date of last issue: 12/06/2023
Date of first issue: 10/17/2019

IECSC : not determined

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	*	3
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA : 8-hour, time-weighted average
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
5.2	09/28/2024	5060473-00013	Date of first issue: 10/17/2019

in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/28/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8