according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 8.0 09/28/2024 641714-00023 Date of first issue: 05/03/2016

SECTION 1. IDENTIFICATION

Product name : Buserelin Formulation Other means of identification : RECEPTAL (A004062)

RECEPTAL SYNTHETIC GONADOTROPHIN RELEASING

HORMONE (36019)

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc Address : 126 E. Lincoln Avenue

Rahway, New Jersey U.S.A. 07065

Telephone : 908-740-4000 Emergency telephone : 1-908-423-6000

E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization : Category 1

GHS label elements

Hazard pictograms



Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.

Precautionary Statements : Prevention:

P261 Avoid breathing mist or vapors.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P333 + P313 If skin irritation or rash occurs: Get medical atten-

tion.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version **Revision Date:** SDS Number: Date of last issue: 07/06/2024 09/28/2024 641714-00023 Date of first issue: 05/03/2016 8.0

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Benzyl alcohol	100-51-6	>= 1 - < 5
Buserelin	68630-75-1	< 0.1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled, remove to fresh air. If inhaled

Get medical attention if symptoms occur.

In case of skin contact In case of contact, immediately flush skin with soap and plenty

of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse. : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed If swallowed, DO NOT induce vomiting.

> Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms

In case of eye contact

delayed

May cause an allergic skin reaction. and effects, both acute and

Protection of first-aiders First Aid responders should pay attention to self-protection,

> and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

> Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 8.0 09/28/2024 641714-00023 Date of first issue: 05/03/2016

Hazardous combustion prod: :

ucts

Carbon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec-:

tive equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material

can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.

Avoid breathing mist or vapors.

Do not swallow.

Avoid contact with eyes.

Handle in accordance with good industrial hygiene and safety

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 8.0 09/28/2024 641714-00023 Date of first issue: 05/03/2016

practice, based on the results of the workplace exposure

assessment

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parame- ters / Permissible	Basis
		exposure)	concentration	
Benzyl alcohol	100-51-6	TWA	10 ppm	US WEEL
Buserelin	68630-75-1	TWA	0.1 μg/m3 (OEB 5)	Internal
		Wipe limit	1 μg/100 cm ²	Internal

Engineering measures

Use closed processing systems or containment technologies to control at source (e.g., glove boxes/isolators) and to prevent leakage of compounds into the workplace. All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment.

No open handling permitted.

Totally enclosed processes and materials transport systems

are required.

Operations require the use of appropriate containment technology designed to prevent leakage of compounds into

the workplace.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and

Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air

supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Consider double gloving.

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 8.0 09/28/2024 641714-00023 Date of first issue: 05/03/2016

Eye protection : Wear safety glasses with side shields or goggles.

If the work environment or activity involves dusty conditions,

mists or aerosols, wear the appropriate goggles.

Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or

aerosols.

Skin and body protection : Work uniform or laboratory coat.

Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets,

disposable suits) to avoid exposed skin surfaces.

Use appropriate degowning techniques to remove potentially

contaminated clothing.

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke.

Contaminated work clothing should not be allowed out of the

workplace.

Wash contaminated clothing before re-use.

The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the

use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid, Aqueous solution

Color : colorless

Odor : No data available

Odor Threshold : No data available

pH : 5.7 - 6.3

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower : No data available

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 8.0 09/28/2024 641714-00023 Date of first issue: 05/03/2016

flammability limit

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : 1.004 g/cm³

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : Not applicable

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : Not applicable

Particle characteristics

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard. Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Can react with strong oxidizing agents.

Conditions to avoid : None known.
Incompatible materials : Oxidizing agents

Hazardous decomposition : No hazardous decomposition products are known.

products

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 8.0 09/28/2024 641714-00023 Date of first issue: 05/03/2016

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Components:

Benzyl alcohol:

Acute oral toxicity : LD50 (Rat): 1,200 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.4 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Buserelin:

Acute oral toxicity : LD50 (Rat): 400 mg/kg

LD50 (Mouse): > 1,000 mg/kg

Acute toxicity (other routes of :

administration)

LD50 (Rat): 36 mg/kg

Application Route: Intravenous

LD50 (Rat): > 500 mg/kg

Application Route: Subcutaneous

LD50 (Mouse): 56 - 78 mg/kg Application Route: Intravenous

LD50 (Dog): > 100 mg/kg

Application Route: Subcutaneous

Skin corrosion/irritation

Not classified based on available information.

Components:

Benzyl alcohol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Buserelin:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 8.0 09/28/2024 641714-00023 Date of first issue: 05/03/2016

Components:

Benzyl alcohol:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Method : OECD Test Guideline 405

Buserelin:

Species : Rabbit

Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Benzyl alcohol:

Test Type : Human repeat insult patch test (HRIPT)

Routes of exposure : Skin contact
Species : Humans
Result : positive

Assessment : Probability or evidence of low to moderate skin sensitization

rate in humans

Buserelin:

Routes of exposure : Dermal Species : Guinea pig

Result : Not a skin sensitizer.

Germ cell mutagenicity

Not classified based on available information.

Components:

Benzyl alcohol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Buserelin:

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 8.0 09/28/2024 641714-00023 Date of first issue: 05/03/2016

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: unscheduled DNA synthesis assay

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Benzyl alcohol:

Species : Mouse
Application Route : Ingestion
Exposure time : 103 weeks

Method : OECD Test Guideline 451

Result : negative

Buserelin:

Species : Rat

Application Route : Subcutaneous Exposure time : 24 Months Result : negative

Target Organs : Uterus (including cervix), Pituitary gland, Testes

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Benzyl alcohol:

Effects on fertility : Test Type: Fertility/early embryonic development

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development: Test Type: Embryo-fetal development

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 8.0 09/28/2024 641714-00023 Date of first issue: 05/03/2016

Species: Mouse

Application Route: Ingestion

Result: negative

Buserelin:

Effects on fertility : Test Type: Fertility/early embryonic development

Species: Rat

Application Route: Subcutaneous Fertility: LOAEL: 0.2 µg/kg Result: Effects on fertility.

Test Type: Fertility/early embryonic development

Species: Mouse, male

Application Route: Subcutaneous Fertility: LOAEL: > 1,000 μg/kg Result: Effects on fertility.

Test Type: Fertility/early embryonic development

Species: Mouse, female

Application Route: Subcutaneous Fertility: LOAEL: 100 µg/kg Result: Effects on fertility.

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Intravenous injection

Developmental Toxicity: LOAEL: $0.4~\mu g/kg$ body weight Result: Embryotoxic effects., Effects on early embryonic

development.

Test Type: Embryo-fetal development

Species: Rabbit

Developmental Toxicity: LOAEL: 0.1 μg/kg body weight Result: Embryotoxic effects., No specific developmental

abnormalities.

Test Type: Embryo-fetal development

Species: Mouse

Developmental Toxicity: NOAEL: 0.1 µg/kg body weight Result: Embryotoxic effects., No effects on F1 offspring.

Reproductive toxicity - As-

. sessment May damage fertility.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version **Revision Date:** SDS Number: Date of last issue: 07/06/2024 8.0 09/28/2024 641714-00023 Date of first issue: 05/03/2016

Repeated dose toxicity

Components:

Benzyl alcohol:

Species Rat NOAEL NOAEL Application Route : 1.072 mg/l

: inhalation (dust/mist/fume)

Exposure time : 28 Days

Method : OECD Test Guideline 412

Buserelin:

Species Rat

LOAEL
Application Route
Exposure time : 0.5 ug/kg/day Subcutaneous Exposure time 14 Days

Species : Rat

LOAEL
Application Route
Exposure time
Target Organs : 0.05 ug/kg/day Subcutaneous 28 Days Target Organs Testis

Species Rabbit NOAEL 20 ug/kg/day Exposure time 4 Weeks

Target Organs Prostate, Pituitary gland, Testis

Species Monkey LOAEL : 5 ug/kg/day

Exposure time 1 y

Target Organs Ovary, Pituitary gland

Species LOAEL Application Route Exposure time Target Organs : Dog : 0.05 mg/kg Subcutaneous : 30 Days

: Pituitary gland, Testis Target Organs

Species Dog LOAEL 0.05 mg/kg Application Route Subcutaneous Exposure time : 6 Months

Target Organs : Reproductive organs

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

Buserelin:

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 09/28/2024 641714-00023 Date of first issue: 05/03/2016 8.0

Inhalation Symptoms: male reproductive effects, female reproductive

effects, reduced libido, Headache, Rash, Gastrointestinal dis-

turbance, mental depression, Local irritation

Remarks: May damage fertility. Based on Human Evidence

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Benzyl alcohol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 460 mg/l

Exposure time: 96 h

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 230 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 770

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 310

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other:

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 51 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Buserelin:

Ecotoxicology Assessment

Acute aquatic toxicity No data available

Chronic aquatic toxicity No data available

Persistence and degradability

Components:

Benzyl alcohol:

Biodegradability Result: Readily biodegradable.

Biodegradation: 92 - 96 %

Exposure time: 14 d

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 8.0 09/28/2024 641714-00023 Date of first issue: 05/03/2016

Bioaccumulative potential

Components:

Benzyl alcohol:

Partition coefficient: n-

octanol/water

: log Pow: 1.05

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 8.0 09/28/2024 641714-00023 Date of first issue: 05/03/2016

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Water 7732-18-5 Benzyl alcohol 100-51-6

The ingredients of this product are reported in the following inventories:

AICS : not determined


DSL : not determined

IECSC : not determined

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)

US WEEL / TWA : 8-hr TWA

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 8.0 09/28/2024 641714-00023 Date of first issue: 05/03/2016

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods: IMO - International Maritime Organization: ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet cy

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 09/28/2024

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8