according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11504907-00004 Date of first issue: 01/22/2025

#### **SECTION 1. IDENTIFICATION**

Product name : Butafosfan (<1%) Formulation

Product code : Prevensa Megabic, Prevensa Megabic Parent

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc Address : 126 E. Lincoln Avenue

Rahway, New Jersey U.S.A. 07065

Telephone : 908-740-4000 Emergency telephone : 1-908-423-6000

E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product Restrictions on use : Not applicable

#### **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Combustible dust

Skin irritation : Category 2

Serious eye damage : Category 1

Other hazards

None known.

GHS label elements

Hazard pictograms :

正型

Signal Word : Danger

Hazard Statements : If small particles are generated during further processing, han-

dling or by other means, may form combustible dust concentra-

tions in air.

H315 Causes skin irritation.

H318 Causes serious eye damage.

Supplemental Hazard State-

ments

Corrosive to the respiratory tract.

Precautionary Statements : Prevention:

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves, eye protection and face protec-

according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/14/2025

 4.0
 06/18/2025
 11504907-00004
 Date of first issue: 01/22/2025

tion.

#### Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER.

P332 + P313 If skin irritation occurs: Get medical attention. P362 + P364 Take off contaminated clothing and wash it before

reuse.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

### Components

| Chemical name     | CAS No./Unique<br>ID | Concentration (% w/w) | Trade secret |
|-------------------|----------------------|-----------------------|--------------|
| Calcium diformate | 544-17-2*            | >= 30 - <= 60         | TSC          |
| Phosphoric acid   | 7664-38-2*           | >= 10 - <= 30         | TSC          |
| Citric acid       | 77-92-9*             | >= 7 - <= 13          | TSC          |
| L-Malic acid      | 97-67-6*             | >= 7 - <= 13          | TSC          |
| Fumaric acid      | 110-17-8*            | >= 7 - <= 13          | TSC          |
| Formic acid       | 64-18-6*             | >= 1 - <= 5           | TSC          |
| Butafosfan        | 17316-67-5*          | >= 0.1 - <= 1         | TSC          |

<sup>\*</sup> Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

### **SECTION 4. FIRST AID MEASURES**

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

according to the OSHA Hazard Communication Standard



## Butafosfan (<1%) Formulation

Version **Revision Date:** SDS Number: Date of last issue: 04/14/2025 06/18/2025 11504907-00004 Date of first issue: 01/22/2025 4.0

for at least 15 minutes.

Causes skin irritation.

If easy to do, remove contact lens, if worn.

Get medical attention immediately.

If swallowed If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur.

Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

Protection of first-aiders

Causes serious eye damage.

Corrosive to the respiratory tract. First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician Treat symptomatically and supportively.

### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray

> Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Avoid generating dust; fine dust dispersed in air in sufficient

concentrations, and in the presence of an ignition source is a

potential dust explosion hazard.

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Carbon oxides Metal oxides

Oxides of phosphorus

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec: : tive equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

**Environmental precautions** Avoid release to the environment.

> Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11504907-00004 Date of first issue: 01/22/2025

cannot be contained.

Methods and materials for containment and cleaning up

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

Avoid dispersal of dust in the air (i.e., clearing dust surfaces

with compressed air).

Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

#### **SECTION 7. HANDLING AND STORAGE**

Technical measures : Static electricity may accumulate and ignite suspended dust

causing an explosion.

Provide adequate precautions, such as electrical grounding

and bonding, or inert atmospheres.

Local/Total ventilation Advice on safe handling Use only with adequate ventilation.

Do not get on skin or clothing.

Do not breathe dust. Do not swallow. Do not get in eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Keep container tightly closed.

Minimize dust generation and accumulation. Keep container closed when not in use. Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Keep tightly closed.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### Ingredients with workplace control parameters

inert or nuisance dust 50 Million particles per cubic foot

Value type (Form of exposure): TWA (total dust)

Basis: OSHA Z-3

according to the OSHA Hazard Communication Standard



## Butafosfan (<1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 06/18/2025 11504907-00004 Date of first issue: 01/22/2025 4.0

15 mg/m<sup>3</sup>

Value type (Form of exposure): TWA (total dust)

Basis: OSHA Z-3

5 mg/m<sup>3</sup>

Value type (Form of exposure): TWA (respirable fraction)

Basis: OSHA Z-3

15 Million particles per cubic foot

Value type (Form of exposure): TWA (respirable fraction)

Basis: OSHA Z-3

Dust, nuisance dust and par-

ticulates

10 mg/m<sup>3</sup>

Value type (Form of exposure): PEL (Total dust)

Basis: CAL PEL

5 mg/m<sup>3</sup>

Value type (Form of exposure): PEL (respirable dust fraction)

Basis: CAL PEL

| Components      | CAS-No.   | Value type<br>(Form of<br>exposure) | Control parameters / Permissible concentration | Basis     |
|-----------------|-----------|-------------------------------------|--|-----------|
| Phosphoric acid | 7664-38-2 | TWA                                 | 1 mg/m³  | ACGIH     |
|                 |           | STEL                                | 3 mg/m³  | ACGIH     |
|                 |           | TWA                                 | 1 mg/m³  | NIOSH REL |
|                 |           | ST                                  | 3 mg/m³  | NIOSH REL |
|                 |           | TWA                                 | 1 mg/m³  | OSHA Z-1  |
| Formic acid     | 64-18-6   | TWA                                 | 5 ppm  | ACGIH     |
|                 |           | TWA                                 | 5 ppm<br>9 mg/m³                               | NIOSH REL |
|                 |           | TWA                                 | 5 ppm<br>9 mg/m³                               | OSHA Z-1  |

### **Engineering measures**

All engineering controls should be implemented by facility design and operated in accordance with GMP principles to

protect products, workers, and the environment.

Containment technologies suitable for controlling compounds are required to control at source and to prevent migration of

the compound to uncontrolled areas (e.g., open-face

containment devices). Minimize open handling.

#### Personal protective equipment

Respiratory protection

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where

concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any

hazardous chemical is limited. Use a positive pressure air

according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11504907-00004 Date of first issue: 01/22/2025

supplied respirator if there is any potential for uncontrolled

release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Consider double gloving.

Eye protection : Wear safety glasses with side shields or goggles.

If the work environment or activity involves dusty conditions,

mists or aerosols, wear the appropriate goggles.

Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or

aerosols.

Skin and body protection : Work uniform or laboratory coat.

Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to suit appeared skip surfaces.

disposable suits) to avoid exposed skin surfaces.

Use appropriate degowning techniques to remove potentially

contaminated clothing.

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the

use of administrative controls.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : powder

Color : white

Odor : No data available

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : May form explosive dust-air mixture during processing,

according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11504907-00004 Date of first issue: 01/22/2025

handling or other means.

Flammability (liquids) : Not applicable

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : No data available

Density : No data available

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle characteristics

Particle size : No data available

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard. Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

May form explosive dust-air mixture during processing,

handling or other means.

Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Avoid dust formation.

Oxidizing agents

Incompatible materials
Hazardous decomposition

No hazardous decomposition products are known.

according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

Version 4.0

Revision Date: 06/18/2025

SDS Number: 11504907-00004

Date of last issue: 04/14/2025 Date of first issue: 01/22/2025

products

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

### Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

### **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute oral toxicity : Acute toxicity estimate: 2,725 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

**Components:** 

**Calcium diformate:** 

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Phosphoric acid:

Acute oral toxicity : LD50 (Rat): 2,000 mg/kg

Method: OECD Test Guideline 423

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Citric acid:

Acute oral toxicity : LD50 (Mouse): 5,400 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

L-Malic acid:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Remarks: Based on data from similar materials

according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11504907-00004 Date of first issue: 01/22/2025

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Remarks: Based on data from similar materials

Fumaric acid:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 1.306 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Formic acid:

Acute oral toxicity : Acute toxicity estimate (Humans): 500 mg/kg

Method: Expert judgment

Acute inhalation toxicity : LC50 (Rat): 7.4 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Remarks: Based on data from similar materials

**Butafosfan:** 

Acute oral toxicity : LD50 (Mouse): 16,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

**Components:** 

**Calcium diformate:** 

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Phosphoric acid:

Result : Corrosive after 3 minutes to 1 hour of exposure

Remarks : Based on national or regional regulation.

Citric acid:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

L-Malic acid:

Species : Rabbit

according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11504907-00004 Date of first issue: 01/22/2025

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Fumaric acid:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Formic acid:

Result : Corrosive after 3 minutes or less of exposure

Remarks : Based on extreme pH

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Calcium diformate:

Species : Rabbit

Result : Irreversible effects on the eye
Method : OECD Test Guideline 405

Phosphoric acid:

Species : Rabbit

Result : Irreversible effects on the eye

Citric acid:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Method : OECD Test Guideline 405

L-Malic acid:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Fumaric acid:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Method : OECD Test Guideline 405

Formic acid:

Result : Irreversible effects on the eye Remarks : Based on skin corrosivity.

according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11504907-00004 Date of first issue: 01/22/2025

#### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

#### Components:

#### Calcium diformate:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Remarks : Based on data from similar materials

#### L-Malic acid:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Remarks : Based on data from similar materials

#### Fumaric acid:

Test Type : Maximization Test Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

### Formic acid:

Test Type : Buehler Test Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

### Germ cell mutagenicity

Not classified based on available information.

### **Components:**

### Calcium diformate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in Drosophila mel-

anogaster (in vivo)

according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11504907-00004 Date of first issue: 01/22/2025

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Phosphoric acid:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Citric acid:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: in vitro micronucleus test

Result: positive

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: Ingestion

Result: negative

L-Malic acid:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Fumaric acid:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

according to the OSHA Hazard Communication Standard



## Butafosfan (<1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11504907-00004 Date of first issue: 01/22/2025

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Formic acid:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in Drosophila mel-

anogaster (in vivo)

Application Route: Ingestion Method: OECD Test Guideline 477

Result: negative

Carcinogenicity

Not classified based on available information.

**Components:** 

Formic acid:

Species : Rat
Application Route : Ingestion
Exposure time : 104 weeks
Result : negative

Remarks : Based on data from similar materials

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Calcium diformate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development: Test Type: Embryo-fetal development

according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11504907-00004 Date of first issue: 01/22/2025

Species: Rabbit

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

Phosphoric acid:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Method: OECD Test Guideline 422

Result: negative

Citric acid:

Effects on fetal development : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

L-Malic acid:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Formic acid:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rabbit

Application Route: Ingestion

according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11504907-00004 Date of first issue: 01/22/2025

Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

### STOT-single exposure

Corrosive to the respiratory tract.

#### Components:

#### Citric acid:

Assessment : May cause respiratory irritation.

### STOT-repeated exposure

Not classified based on available information.

### Repeated dose toxicity

### **Components:**

#### Calcium diformate:

Species : Rat

NOAEL : 3,000 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

Method : OECD Test Guideline 408

Remarks : Based on data from similar materials

### Phosphoric acid:

Species : Rat

NOAEL : 250 mg/kg

Application Route : Ingestion

Exposure time : 40 - 52 Days

Method : OECD Test Guideline 422

### Citric acid:

Species : Rat

NOAEL : 4,000 mg/kg LOAEL : 8,000 mg/kg Application Route : Ingestion Exposure time : 10 Days

#### L-Malic acid:

Species : Rat

NOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 104 Weeks

Remarks : Based on data from similar materials

Fumaric acid:

Species : Rat

according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 06/18/2025 11504907-00004 Date of first issue: 01/22/2025 4.0

NOAEL 600 mg/kg Application Route Ingestion Exposure time 2 y

Formic acid:

Species Rat NOAEL 400 mg/kg Application Route Ingestion Exposure time 52 Weeks

Remarks Based on data from similar materials

**Aspiration toxicity** 

Not classified based on available information.

#### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

### **Components:**

Calcium diformate:

Toxicity to fish LC0 (Danio rerio (zebra fish)): >= 1,000 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 48 h

Method: EPA-660/3-75-009

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): >

1,000 mg/l

Exposure time: 72 h

Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 500

mg/l

Exposure time: 72 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other:

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): >= 100 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Toxicity to microorganisms NOEC: >= 22.1 mg/l

Exposure time: 28 d

Remarks: Based on data from similar materials

Phosphoric acid:

Toxicity to fish LC50 (Oryzias latipes (Japanese medaka)): > 100 mg/l

Exposure time: 96 h

according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 06/18/2025 11504907-00004 Date of first issue: 01/22/2025 4.0

Method: OECD Test Guideline 203

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): > 100 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms EC50: > 100 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Citric acid:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,535 mg/l

Exposure time: 24 h

L-Malic acid:

Toxicity to fish LC50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Test substance: Neutralized product Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): > 1

mg/l

Exposure time: 72 h

Test substance: Neutralized product Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

EC50 (activated sludge): > 100 mg/l Foxicity to microorganisms

Exposure time: 3 h

according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11504907-00004 Date of first issue: 01/22/2025

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Fumaric acid:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 100

mq/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 300 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Formic acid:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 130 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 365 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): 1,240

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

EC10 (Pseudokirchneriella subcapitata (green algae)): 295

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11504907-00004 Date of first issue: 01/22/2025

Toxicity to microorganisms : NOEC: 72 mg/l

Exposure time: 13 d

**Butafosfan:** 

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Toxic effects cannot be excluded

Chronic aquatic toxicity : Toxic effects cannot be excluded

Persistence and degradability

**Components:** 

Calcium diformate:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 86 % Exposure time: 28 d

Method: OECD Test Guideline 306

Remarks: Based on data from similar materials

Citric acid:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 97 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Fumaric acid:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 67.5 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Formic acid:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 100 % Exposure time: 28 d

Method: OECD Test Guideline 301C

**Bioaccumulative potential** 

**Components:** 

**Calcium diformate:** 

Partition coefficient: n- : log Pow: -2.3 - -1.9

octanol/water Remarks: Based on data from similar materials

Citric acid:

Partition coefficient: n- : log Pow: -1.72

according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 06/18/2025 11504907-00004 Date of first issue: 01/22/2025 4.0

octanol/water

L-Malic acid:

Partition coefficient: n-: log Pow: -1.68

octanol/water Remarks: Calculation

Fumaric acid:

Partition coefficient: nlog Pow: 0.46

octanol/water Formic acid:

octanol/water

Partition coefficient: nlog Pow: -2.1

Mobility in soil

No data available

Other adverse effects

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS** 

**Disposal methods** 

Waste from residues Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Empty containers should be taken to an approved waste Contaminated packaging

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

**SECTION 14. TRANSPORT INFORMATION** 

International Regulations

**UNRTDG** 

**UN** number UN 3453

PHOSPHORIC ACID, SOLID MIXTURE Proper shipping name

Class 8 Packing group Ш Labels 8 Environmentally hazardous no

**IATA-DGR** 

UN/ID No.

Proper shipping name Phosphoric acid, solid Mixture

Class Ш Packing group

Corrosive Labels Packing instruction (cargo 864

aircraft)

Packing instruction (passen-

860

ger aircraft)

**IMDG-Code** 

**UN** number UN 3453

according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11504907-00004 Date of first issue: 01/22/2025

Proper shipping name : PHOSPHORIC ACID, SOLID MIXTURE

Class : 8
Packing group : III
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : no

### Transport in bulk according to IMO instruments

Not applicable for product as supplied.

#### **Domestic regulation**

**49 CFR** 

UN/ID/NA number : UN 3453

Proper shipping name : Phosphoric acid, solid MIXTURE

Class : 8 Packing group : III

Labels : CORROSIVE

ERG Code : 154 Marine pollutant : no

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### **SECTION 15. REGULATORY INFORMATION**

### **CERCLA Reportable Quantity**

| Components      | CAS-No.   | Component RQ   Calculated product RQ |       |
|-----------------|-----------|--------------------------------------|-------|
|                 |           | (lbs)                                | (lbs) |
| Phosphoric acid | 7664-38-2 | 5000                                 | 26315 |
| Fumaric acid    | 110-17-8  | 5000                                 | 55555 |

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Combustible dust

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Formic acid 64-18-6 >= 1 - < 5 %

#### **US State Regulations**

### Pennsylvania Right To Know

Calcium diformate 544-17-2

according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

| Version<br>4.0  | Revision Date: 06/18/2025                      | SDS Number:<br>11504907-00004 | Date of last issue: 04/14/2025<br>Date of first issue: 01/22/2025 |  |
|---|--|-------------------------------|---|--|
| Phosphoric acid Citric acid L-Malic acid Fumaric acid Formic acid |  |                               | 7664-38-2<br>77-92-9<br>97-67-6<br>110-17-8<br>64-18-6            |  |
| Calif   | ornia List of Hazardou                         | us Substances                 |   |  |
|   | Phosphoric acid<br>Fumaric acid<br>Formic acid |                               | 7664-38-2<br>110-17-8<br>64-18-6                                  |  |
| Calif   | ornia Permissible Exp                          | osure Limits for Che          | mical Contaminants  |  |
|   | Phosphoric acid                                |                               | 7664-38-2   |  |

### The ingredients of this product are reported in the following inventories:

AICS : not determined

DSL : not determined


IECSC : not determined

### **SECTION 16. OTHER INFORMATION**

Formic acid

#### **Further information**

### NFPA 704:



Special hazard

#### HMIS® IV:



64-18-6

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CAL PEL : California permissible exposure limits for chemical contami-

nants (Title 8, Article 107)

NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11504907-00004 Date of first issue: 01/22/2025

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit : Permissible exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals: ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

**Data Sheet** 

cy, http://echa.europa.eu/

Revision Date : 06/18/2025

according to the OSHA Hazard Communication Standard



## **Butafosfan (<1%) Formulation**

Version Revision Date: SDS Number: Date of last issue: 04/14/2025 4.0 06/18/2025 11504907-00004 Date of first issue: 01/22/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8