according to the OSHA Hazard Communication Standard



# **Lufenuron Premix Formulation**

Version Revision Date: SDS Number: Date of last issue: 05/09/2025 4.0 06/18/2025 11441522-00005 Date of first issue: 09/23/2024

#### **SECTION 1. IDENTIFICATION**

Product name : Lufenuron Premix Formulation

Product code : IMVIXA Premix

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc Address : 126 E. Lincoln Avenue

Rahway, New Jersey U.S.A. 07065

Telephone : 908-740-4000 Emergency telephone : 1-908-423-6000

E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product Restrictions on use : Not applicable

#### **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Combustible dust

Skin sensitization : Category 1

Reproductive toxicity : Category 1B

Specific target organ toxicity

: Category 1 (Central nervous system, Lungs, Liver, Stomach)

- repeated exposure (Oral)

#### Other hazards

Dust contact with the eyes can lead to mechanical irritation.

Contact with dust can cause mechanical irritation or drying of the skin.

#### **GHS** label elements

Hazard pictograms





Signal Word : Danger

Hazard Statements : If small particles are generated during further processing, han-

dling or by other means, may form combustible dust concentra-

tions in air.

H317 May cause an allergic skin reaction. H360D May damage the unborn child.

H372 Causes damage to organs (Central nervous system,

Lungs, Liver, Stomach) through prolonged or repeated exposure

if swallowed.

according to the OSHA Hazard Communication Standard



# **Lufenuron Premix Formulation**

Version Revision Date: SDS Number: Date of last issue: 05/09/2025 4.0 06/18/2025 11441522-00005 Date of first issue: 09/23/2024

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe dust.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear protective gloves, protective clothing, eye protection

and face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P308 + P313 IF exposed or concerned: Get medical attention. P333 + P313 If skin irritation or rash occurs: Get medical atten-

tion.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Starch	9005-25-8*	>= 80 - <= 100	TSC
Lufenuron (ISO)	103055-07-8*	>= 7 - <= 13	TSC
Silicon, amorphous	112945-52-5*	>= 1 - <= 5	TSC

<sup>\*</sup> Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

### **SECTION 4. FIRST AID MEASURES**

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention.

according to the OSHA Hazard Communication Standard



# **Lufenuron Premix Formulation**

Version Revision Date: SDS Number: Date of last issue: 05/09/2025 4.0 06/18/2025 11441522-00005 Date of first issue: 09/23/2024

In case of skin contact : In case of contact, immediately flush skin with soap and plenty

of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : If in eyes, rinse well with water.

Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.

Get medical attention.

Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

Contact with dust can cause mechanical irritation or drying of

the skin.

Dust contact with the eyes can lead to mechanical irritation.

May cause an allergic skin reaction. May damage the unborn child.

Causes damage to organs through prolonged or repeated

exposure if swallowed.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Avoid generating dust; fine dust dispersed in air in sufficient

concentrations, and in the presence of an ignition source is a

potential dust explosion hazard.

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Carbon oxides

Nitrogen oxides (NOx)

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

according to the OSHA Hazard Communication Standard



# **Lufenuron Premix Formulation**

Version Revision Date: SDS Number: Date of last issue: 05/09/2025 4.0 06/18/2025 11441522-00005 Date of first issue: 09/23/2024

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

Avoid dispersal of dust in the air (i.e., clearing dust surfaces

with compressed air).

Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

#### **SECTION 7. HANDLING AND STORAGE**

Technical measures : Static electricity may accumulate and ignite suspended dust

causing an explosion.

Provide adequate precautions, such as electrical grounding

and bonding, or inert atmospheres.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Advice on safe handling : Do not get on skin or clothing.

Do not breathe dust. Do not swallow.

Avoid contact with eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Keep container tightly closed.

Minimize dust generation and accumulation. Keep container closed when not in use. Keep away from heat and sources of ignition.

Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store locked up. Keep tightly closed.

Store in accordance with the particular national regulations.

according to the OSHA Hazard Communication Standard



# **Lufenuron Premix Formulation**

Version Revision Date: SDS Number: Date of last issue: 05/09/2025 4.0 06/18/2025 11441522-00005 Date of first issue: 09/23/2024

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

Self-reactive substances and mixtures

Organic peroxides

Explosives Gases

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

# Ingredients with workplace control parameters

inert or nuisance dust 50 Million particles per cubic foot

Value type (Form of exposure): TWA (total dust)

Basis: OSHA Z-3

15 mg/m<sup>3</sup>

Value type (Form of exposure): TWA (total dust)

Basis: OSHA Z-3

5 mg/m<sup>3</sup>

Value type (Form of exposure): TWA (respirable fraction)

Basis: OSHA Z-3

15 Million particles per cubic foot

Value type (Form of exposure): TWA (respirable fraction)

Basis: OSHA Z-3

Dust, nuisance dust and par-

ticulates

10 mg/m<sup>3</sup>

Value type (Form of exposure): PEL (Total dust)

Basis: CAL PEL

5 mg/m<sup>3</sup>

Value type (Form of exposure): PEL (respirable dust fraction)

Basis: CAL PEL

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis	
Starch	9005-25-8	TWA	10 mg/m³	ACGIH	
		TWA (Respirable)	5 mg/m³	NIOSH REL	
		TWA (total)	10 mg/m <sup>3</sup>	NIOSH REL	
		TWA (total dust)	15 mg/m³	OSHA Z-1	
		TWA (respirable fraction)	5 mg/m³	OSHA Z-1	
Lufenuron (ISO)	103055-07-8	TWA	200 μg/m3 (OEB 2)	Internal	
	Further information: DSEN				
		Wipe limit	100 μg/100 cm2	Internal	
Silicon, amorphous	112945-52-5	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3	

according to the OSHA Hazard Communication Standard



# **Lufenuron Premix Formulation**

Version **Revision Date:** SDS Number: Date of last issue: 05/09/2025 06/18/2025 11441522-00005 Date of first issue: 09/23/2024 4.0

	(Silica)	
TWA (Dust)	80 mg/m3	OSHA Z-3
	/ %SiO2	
	(Silica)	
TWA	6 mg/m <sup>3</sup>	NIOSH REL
	(Silica)	

Engineering measures

Use feasible engineering controls to minimize exposure to

compound.

All engineering controls should be implemented by facility design and operated in accordance with GMP principles to

protect products, workers, and the environment.

Personal protective equipment

General and local exhaust ventilation is recommended to Respiratory protection

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn.

Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material Chemical-resistant gloves

Eye protection Wear safety glasses with side shields or goggles.

If the work environment or activity involves dusty conditions,

mists or aerosols, wear the appropriate goggles.

Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or

aerosols.

Skin and body protection

Work uniform or laboratory coat. Hygiene measures

If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke.

Contaminated work clothing should not be allowed out of the

Wash contaminated clothing before re-use.

The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the

use of administrative controls.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES** 

Appearance powder

Color White to light yellow

according to the OSHA Hazard Communication Standard



# **Lufenuron Premix Formulation**

Version Revision Date: SDS Number: Date of last issue: 05/09/2025 4.0 06/18/2025 11441522-00005 Date of first issue: 09/23/2024

Odor : No data available

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : May form explosive dust-air mixture during processing,

handling or other means.

Flammability (liquids) : Not applicable

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : No data available

Density : No data available

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

according to the OSHA Hazard Communication Standard



# **Lufenuron Premix Formulation**

Version Revision Date: SDS Number: Date of last issue: 05/09/2025 4.0 06/18/2025 11441522-00005 Date of first issue: 09/23/2024

Particle characteristics

Particle size : No data available

# **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard. Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

May form explosive dust-air mixture during processing,

handling or other means.

Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Avoid dust formation.

Oxidizing agents

Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

### **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

**Components:** 

Starch:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Lufenuron (ISO):

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

LD50 (Mouse): > 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 2,350 mg/m<sup>3</sup>

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

according to the OSHA Hazard Communication Standard



# **Lufenuron Premix Formulation**

Version Revision Date: SDS Number: Date of last issue: 05/09/2025 4.0 06/18/2025 11441522-00005 Date of first issue: 09/23/2024

П

Silicon, amorphous:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 2.08 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

**Components:** 

Lufenuron (ISO):

Species : Rabbit
Method : Draize Test
Result : No skin irritation

Silicon, amorphous:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Starch:

Species : Rabbit

Result : No eye irritation

Lufenuron (ISO):

Species : Rabbit

Result : No eye irritation
Method : Draize Test

Silicon, amorphous:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

according to the OSHA Hazard Communication Standard



# **Lufenuron Premix Formulation**

Version Revision Date: SDS Number: Date of last issue: 05/09/2025 4.0 06/18/2025 11441522-00005 Date of first issue: 09/23/2024

Remarks : Based on data from similar materials

#### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

### Respiratory sensitization

Not classified based on available information.

### Components:

#### Starch:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

# Lufenuron (ISO):

Test Type : Maximization Test

Species : Guinea pig

Assessment : May cause sensitization by skin contact.

Result : Sensitizer

#### Germ cell mutagenicity

Not classified based on available information.

#### **Components:**

#### Starch:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

### Lufenuron (ISO):

Genotoxicity in vitro : Test Type: Ames test

Result: negative

Test Type: Mouse Lymphoma Test system: Chinese hamster cells

Result: negative

Test Type: Cytogenetic assay

Test system: Chinese hamster ovary cells

Result: negative

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro) Test system: rat hepatocytes

Result: negative

Test system: Human lymphocytes

Result: negative

according to the OSHA Hazard Communication Standard



# **Lufenuron Premix Formulation**

Version Revision Date: SDS Number: Date of last issue: 05/09/2025 4.0 06/18/2025 11441522-00005 Date of first issue: 09/23/2024

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse Result: negative

Test Type: Unscheduled DNA synthesis test (UDS) in testicu-

lar cells Species: Rat Result: negative

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

Silicon, amorphous:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

#### Carcinogenicity

Not classified based on available information.

### Components:

#### Lufenuron (ISO):

Species : Rat
Application Route : Ingestion
Exposure time : 18 month(s)
Result : negative

Carcinogenicity - Assess-

ment

Weight of evidence does not support classification as a car-

cinogen

Silicon, amorphous:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Remarks : Based on data from similar materials

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**No component of this product present at levels greater than or equal to 0.1% is

according to the OSHA Hazard Communication Standard



# **Lufenuron Premix Formulation**

Version Revision Date: SDS Number: Date of last issue: 05/09/2025 4.0 06/18/2025 11441522-00005 Date of first issue: 09/23/2024

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

#### Reproductive toxicity

May damage the unborn child.

#### Components:

#### Lufenuron (ISO):

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Oral

General Toxicity Parent: NOAEL: 8.3 mg/kg wet weight Early Embryonic Development: NOAEL: 20.9 mg/kg body

weiaht

Result: Animal testing did not show any effects on fertility.

Effects on fetal development : Test Type: Development

Species: Rat

Application Route: Oral

General Toxicity Maternal: NOAEL: 500 mg/kg body weight Developmental Toxicity: NOAEL: 1,000 mg/kg body weight

Symptoms: No adverse effects.

Remarks: No significant adverse effects were reported

Test Type: Fertility/early embryonic development

Species: Rat

Application Route: Ingestion

General Toxicity Maternal: NOAEL: 20.9 mg/kg body weight

Embryo-fetal toxicity.: 8.3 mg/kg body weight

Result: Fetal abnormalities.

Reproductive toxicity - As-

sessment

Clear evidence of adverse effects on development, based on

animal experiments.

# Silicon, amorphous:

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

#### STOT-single exposure

Not classified based on available information.

### **Components:**

### Lufenuron (ISO):

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

according to the OSHA Hazard Communication Standard



# **Lufenuron Premix Formulation**

Version Revision Date: SDS Number: Date of last issue: 05/09/2025 06/18/2025 11441522-00005 Date of first issue: 09/23/2024 4.0

#### STOT-repeated exposure

Causes damage to organs (Central nervous system, Lungs, Liver, Stomach) through prolonged or repeated exposure if swallowed.

### Components:

### Lufenuron (ISO):

Routes of exposure : Oral

: Central nervous system, Lungs, Liver, Stomach Target Organs

: Shown to produce significant health effects in animals at con-Assessment

centrations of 10 mg/kg bw or less.

#### Repeated dose toxicity

### **Components:**

#### Starch:

Species

NOAEL >= 2,000 mg/kgApplication Route Skin contact Exposure time : 28 Days

Method : OECD Test Guideline 410

#### Lufenuron (ISO):

Species Rat

NOAEL 5.34 mg/kg Application Route : oral (feed) : 4 Months

Target Organs : Central nervous system, digestive system

Symptoms : central nervous system effects

Rat

Species
NOAEL
Application Route 1.93 mg/kg oral (feed)

: 2 y

Symptoms central nervous system effects, Convulsions

Species
NOAEL
Application Route
Exposure time
Target Organs
Symptoms Mouse : 2.12 mg/kg : oral (feed) : 18 Months

: Central nervous system, Liver, Prostate Symptoms central nervous system effects, Convulsions

Species
NOAEL
Application Route : Species Dog 7.02 mg/kg oral (feed)

1 y

Central nervous system, Liver, Lungs Symptoms Convulsions, Fatality, Irregularities

according to the OSHA Hazard Communication Standard



# **Lufenuron Premix Formulation**

Version Revision Date: SDS Number: Date of last issue: 05/09/2025 4.0 06/18/2025 11441522-00005 Date of first issue: 09/23/2024

Silicon, amorphous:

Species : Rat NOAEL : 1.3 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 13 Weeks

Remarks : Based on data from similar materials

**Aspiration toxicity** 

Not classified based on available information.

**Experience with human exposure** 

**Components:** 

Lufenuron (ISO):

General Information : Remarks: May be harmful if swallowed.

May cause neurotoxic effects.

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

#### **Components:**

Lufenuron (ISO):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 73,100 μg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

LC50 (Oncorhynchus mykiss (rainbow trout)): > 29,000 µg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

LC50 (Oncorhynchus mykiss (rainbow trout)): 370 µg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Americamysis): 0.042 µg/l

Exposure time: 96 h

Method: US-EPA OPPTS 850.1035

EC50 (Daphnia magna (Water flea)): 0.41 µg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Raphidocelis subcapitata (freshwater green alga)): 209

Exposure time: 72 h

μg/l

exposure time. 72 fr

Method: OECD Test Guideline 201

EC50 (Scenedesmus subspicatus): 17 μg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

according to the OSHA Hazard Communication Standard



# **Lufenuron Premix Formulation**

Version Revision Date: SDS Number: Date of last issue: 05/09/2025 4.0 06/18/2025 11441522-00005 Date of first issue: 09/23/2024

Toxicity to fish (Chronic tox-

NOEC (Oncorhynchus mykiss (rainbow trout)): 80 μg/l

Exposure time: 33 d

Method: OECD Test Guideline 210

NOEC (Oncorhynchus mykiss (rainbow trout)): 20 µg/l

Exposure time: 359 d

Method: OECD Test Guideline 229

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 8.38 µg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

NOEC (Daphnia magna (Water flea)): 90 μg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

NOEC (Chironomus riparius (harlequin fly)): 2 µg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Silicon, amorphous:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 10,000 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 24 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): > 10,000

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEC (Desmodesmus subspicatus (green algae)): 10,000

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Persistence and degradability

No data available

Bioaccumulative potential

**Components:** 

Lufenuron (ISO):

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)

according to the OSHA Hazard Communication Standard



# **Lufenuron Premix Formulation**

Version Revision Date: SDS Number: Date of last issue: 05/09/2025 4.0 06/18/2025 11441522-00005 Date of first issue: 09/23/2024

> Bioconcentration factor (BCF): 28 Method: OECD Test Guideline 305

Partition coefficient: n-

octanol/water

log Pow: 5.12

Mobility in soil

Components:

Lufenuron (ISO):

Distribution among environ-

mental compartments

: log Koc: 5.38

Method: OECD Test Guideline 106

Other adverse effects

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS** 

**Disposal methods** 

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

**SECTION 14. TRANSPORT INFORMATION** 

International Regulations

**UNRTDG** 

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Lufenuron (ISO))

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Lufenuron (ISO))

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo

aircraft)

Packing instruction (passen: :

956

956

ger aircraft)

Environmentally hazardous : yes

**IMDG-Code** 

16 / 20

according to the OSHA Hazard Communication Standard



# **Lufenuron Premix Formulation**

Version Revision Date: SDS Number: Date of last issue: 05/09/2025 4.0 06/18/2025 11441522-00005 Date of first issue: 09/23/2024

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Lufenuron (ISO))

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

#### Transport in bulk according to IMO instruments

Not applicable for product as supplied.

#### **Domestic regulation**

**49 CFR** 

UN/ID/NA number : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Lufenuron (ISO))

Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171

Marine pollutant : yes(Lufenuron (ISO))

Remarks : Above applies only to containers over 119 gallons or 450

liters.

Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO. Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### **SECTION 15. REGULATORY INFORMATION**

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Combustible dust

Respiratory or skin sensitization

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

according to the OSHA Hazard Communication Standard



# **Lufenuron Premix Formulation**

Version Revision Date: SDS Number: Date of last issue: 05/09/2025 4.0 06/18/2025 11441522-00005 Date of first issue: 09/23/2024

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### **US State Regulations**

#### Pennsylvania Right To Know

Starch 9005-25-8 Lufenuron (ISO) 103055-07-8

#### **California Permissible Exposure Limits for Chemical Contaminants**

 Starch
 9005-25-8

 Silicon, amorphous
 112945-52-5

### The ingredients of this product are reported in the following inventories:

AICS : not determined


DSL : not determined

IECSC : not determined

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA 704:



Special hazard

#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CAL PEL : California permissible exposure limits for chemical contami-

nants (Title 8, Article 107)

NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

according to the OSHA Hazard Communication Standard



# **Lufenuron Premix Formulation**

Version Revision Date: SDS Number: Date of last issue: 05/09/2025 4.0 06/18/2025 11441522-00005 Date of first issue: 09/23/2024

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

ACGIH / TWA : 8-hour, time-weighted average CAL PEL / PEL : Permissible exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Olasat

**Revision Date** 

Data Sheet cy, http://echa.europa.eu/

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

: 06/18/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

according to the OSHA Hazard Communication Standard



# **Lufenuron Premix Formulation**

Version Revision Date: SDS Number: Date of last issue: 05/09/2025 4.0 06/18/2025 11441522-00005 Date of first issue: 09/23/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8