according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 7.1 09/30/2023 42862-00021 Date of first issue: 01/06/2015

SECTION 1. IDENTIFICATION

Product name : Vorinostat Formulation

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc Address : 126 E. Lincoln Avenue

Rahway, New Jersey U.S.A. 07065

Telephone : 908-740-4000 Emergency telephone : 1-908-423-6000

E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Pharmaceutical Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Combustible dust

Germ cell mutagenicity : Category 2

Reproductive toxicity : Category 1B

Specific target organ toxicity

- repeated exposure (Oral)

Category 1 (Blood, thymus gland, Bone marrow, spleen, Gastro-

intestinal tract)

GHS label elements

Hazard pictograms



Signal Word : Danger

Hazard Statements : If small particles are generated during further processing, han-

dling or by other means, may form combustible dust concentra-

tions in air.

H341 Suspected of causing genetic defects.

H360FD May damage fertility. May damage the unborn child. H372 Causes damage to organs (Blood, thymus gland, Bone marrow, spleen, Gastrointestinal tract) through prolonged or

repeated exposure if swallowed.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version **Revision Date:** SDS Number: Date of last issue: 04/04/2023 09/30/2023 42862-00021 Date of first issue: 01/06/2015 7.1

P260 Do not breathe dust.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P280 Wear protective gloves, protective clothing, eye protection

and face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

Other hazards

Dust contact with the eyes can lead to mechanical irritation.

Contact with dust can cause mechanical irritation or drying of the skin.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)	
Vorinostat	149647-78-9	>= 50 - < 70	
Cellulose	9004-34-6	>= 20 - < 30	

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled If inhaled, remove to fresh air.

Get medical attention.

In case of skin contact In case of contact, immediately flush skin with soap and plenty

of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse. If in eyes, rinse well with water.

Get medical attention if irritation develops and persists.

If swallowed If swallowed, DO NOT induce vomiting.

Get medical attention.

Rinse mouth thoroughly with water.

Most important symptoms

In case of eye contact

and effects, both acute and

delayed

Suspected of causing genetic defects.

May damage fertility. May damage the unborn child. Causes damage to organs through prolonged or repeated

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 7.1 09/30/2023 42862-00021 Date of first issue: 01/06/2015

exposure if swallowed.

Contact with dust can cause mechanical irritation or drying of

the skin.

Dust contact with the eyes can lead to mechanical irritation. First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

Protection of first-aiders

media

None known.

Specific hazards during fire

fighting

Avoid generating dust; fine dust dispersed in air in sufficient

concentrations, and in the presence of an ignition source is a

potential dust explosion hazard.

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Carbon oxides

Metal oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

Avoid dispersal of dust in the air (i.e., clearing dust surfaces

with compressed air).

Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Local or national regulations may apply to releases and

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 7.1 09/30/2023 42862-00021 Date of first issue: 01/06/2015

disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : Static electricity may accumulate and ignite suspended dust

causing an explosion.

Provide adequate precautions, such as electrical grounding

and bonding, or inert atmospheres.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Advice on safe handling : Do not get on skin or clothing.

Do not breathe dust.
Do not swallow.

Avoid contact with eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Keep container tightly closed.

Minimize dust generation and accumulation. Keep container closed when not in use. Keep away from heat and sources of ignition.

Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store locked up. Keep tightly closed.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

Self-reactive substances and mixtures

Organic peroxides

Explosives Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

inert or nuisance dust 50 Million particles per cubic foot

Value type (Form of exposure): TWA (total dust)

Basis: OSHA Z-3

15 mg/m³

Value type (Form of exposure): TWA (total dust)

Basis: OSHA Z-3

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 7.1 09/30/2023 42862-00021 Date of first issue: 01/06/2015

5 mg/m³

Value type (Form of exposure): TWA (respirable fraction)

Basis: OSHA Z-3

15 Million particles per cubic foot

Value type (Form of exposure): TWA (respirable fraction)

Basis: OSHA Z-3

Dust, nuisance dust and par-

ticulates

10 mg/m³

Value type (Form of exposure): PEL (Total dust)

Basis: CAL PEL

5 mg/m³

Value type (Form of exposure): PEL (respirable dust fraction)

Basis: CAL PEL

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Vorinostat	149647-78-9	TWA	5 μg/m ³	Internal
vonnosiai	149047-70-9			
		Wipe limit	50 μg/100 cm ²	Internal
Cellulose	9004-34-6	TWA	10 mg/m ³	ACGIH
		TWA (Res-	5 mg/m ³	NIOSH REL
		pirable)		
		TWA (total)	10 mg/m ³	NIOSH REL
		TWA (total	15 mg/m ³	OSHA Z-1
		dust)	-	
		TWA (respirable fraction)	5 mg/m³	OSHA Z-1

Engineering measures

Minimize workplace exposure concentrations.

Apply measures to prevent dust explosions.

Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Personal protective equipment

Respiratory protection

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and

use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air

hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 7.1 09/30/2023 42862-00021 Date of first issue: 01/06/2015

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:

Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Color : No data available

Odor : odorless

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) : May form explosive dust-air mixture during processing,

handling or other means.

Flammability (liquids) : No data available

Upper explosion limit / Upper

flammability limit

No data available

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 7.1 09/30/2023 42862-00021 Date of first issue: 01/06/2015

Lower explosion limit / Lower :

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : No data available

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard. Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

May form explosive dust-air mixture during processing,

handling or other means.

Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Avoid dust formation.

Incompatible materials

Hazardous decomposition

products

Oxidizing agents

: No hazardous decomposition products are known.

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 7.1 09/30/2023 42862-00021 Date of first issue: 01/06/2015

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: 3,788 mg/kg

Method: Calculation method

Components:

Vorinostat:

Acute oral toxicity : LD50 (Mouse): > 2,000 mg/kg

LD50 (Rat): > 750 mg/kg

Acute toxicity (other routes of :

administration)

LDLo (Mouse): 1,250 mg/kg

Application Route: Intravenous

Exposure time: 4 h

Cellulose:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.8 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Vorinostat:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Vorinostat:

Species : Bovine cornea

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 7.1 09/30/2023 42862-00021 Date of first issue: 01/06/2015

Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Vorinostat:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact Species : Mouse

Result : Not a skin sensitizer.

Germ cell mutagenicity

Suspected of causing genetic defects.

Components:

Vorinostat:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: positive

Test Type: Chromosome aberration test in vitro Test system: Chinese hamster ovary cells

Result: positive

Test Type: Chromosome aberration test in vitro

Test system: Human lymphocytes

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay)
Species: Mouse
Application Route: Oral

Result: positive

Germ cell mutagenicity -

Assessment

Positive result(s) from in vivo mammalian somatic cell muta-

genicity tests.

Cellulose:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay)

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 7.1 09/30/2023 42862-00021 Date of first issue: 01/06/2015

Species: Mouse

Application Route: Ingestion

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Cellulose:

Species : Rat
Application Route : Ingestion
Exposure time : 72 weeks
Result : negative

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

May damage fertility. May damage the unborn child.

Components:

Vorinostat:

Effects on fertility : Test Type: Fertility/early embryonic development

Species: Rat, female Application Route: Oral

Fertility: LOAEL: 15 mg/kg body weight

Result: Preimplantation loss., Increased resorptions.

Test Type: Fertility/early embryonic development

Species: Rat, male Application Route: Oral

Fertility: NOAEL: 150 mg/kg body weight

Result: No effects on fertility.

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Oral

Developmental Toxicity: LOAEL: 50 mg/kg body weight

Result: positive

Test Type: Embryo-fetal development

Species: Rat

Application Route: Oral

Developmental Toxicity: NOAEL: 15 mg/kg body weight

Result: positive

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 7.1 09/30/2023 42862-00021 Date of first issue: 01/06/2015

Test Type: Embryo-fetal development

Species: Rabbit Application Route: Oral

Developmental Toxicity: LOAEL: 150 mg/kg body weight

Result: Embryotoxic effects.

Test Type: Embryo-fetal development

Species: Rabbit Application Route: Oral

Developmental Toxicity: NOAEL: 50 mg/kg body weight

Result: Embryotoxic effects.

Test Type: Embryo-fetal development

Species: Rabbit Application Route: Oral

Developmental Toxicity: LOAEL: 15 mg/kg body weight

Result: Malformations were observed.

Reproductive toxicity - As-

sessment

Clear evidence of adverse effects on sexual function and fertility, based on animal experiments., Clear evidence of

adverse effects on development, based on animal

experiments.

Cellulose:

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Fertility/early embryonic development

Species: Rat

Application Route: Ingestion

Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Blood, thymus gland, Bone marrow, spleen, Gastrointestinal tract) through prolonged or repeated exposure if swallowed.

Components:

Vorinostat:

Routes of exposure : Ingestion

Target Organs : Blood, thymus gland, Bone marrow, spleen, Gastrointestinal

tract

Assessment : Causes damage to organs through prolonged or repeated

exposure.

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 7.1 09/30/2023 42862-00021 Date of first issue: 01/06/2015

Repeated dose toxicity

Components:

Vorinostat:

Species : Rat
LOAEL : 20 mg/kg
Application Route : Oral
Exposure time : 6 Months

Target Organs : Blood, thymus gland, Bone marrow, spleen

Species : Dog
NOAEL : 60 mg/kg
LOAEL : 160 mg/kg
Application Route : Oral
Exposure time : 6 Months

Target Organs : Gastrointestinal tract

Species : Dog
NOAEL : 40 mg/kg
LOAEL : 100 mg/kg
Application Route : Oral
Exposure time : 4 Weeks
Target Organs : Blood

Cellulose:

Species : Rat

NOAEL : >= 9,000 mg/kg Application Route : Ingestion

Exposure time : 90 Days

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

Vorinostat:

Ingestion : Symptoms: Diarrhea, Fatigue, Nausea, anorexia

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Vorinostat:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 10 mg/l

Exposure time: 96 h

LC50 (Cyprinodon variegatus (sheepshead minnow)): > 10

mg/l

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 7.1 09/30/2023 42862-00021 Date of first issue: 01/06/2015

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10 mg/l

Exposure time: 48 h

EC50 (Americamysis): 7.4 mg/l

Exposure time: 96 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 0.183

mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.011

mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOEC (Pimephales promelas (fathead minnow)): 1.5 mg/l

Exposure time: 33 d

Method: OECD Test Guideline 210

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.15 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: > 1,000 mg/l

Exposure time: 3 h

Test Type: Respiration inhibition

Cellulose:

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 100 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

Persistence and degradability

Components:

Vorinostat:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 39.5 % Exposure time: 28 d

Method: OECD Test Guideline 314

Cellulose:

Biodegradability : Result: Readily biodegradable.

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 7.1 09/30/2023 42862-00021 Date of first issue: 01/06/2015

Bioaccumulative potential

Components:

Vorinostat:

Partition coefficient: n-

octanol/water

log Pow: 1.42

Mobility in soil

Components:

Vorinostat:

Distribution among environ-

mental compartments

Other adverse effects

No data available

log Koc: 3.37

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Vorinostat)

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Vorinostat)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo

aircraft)

956

Packing instruction (passen-

ger aircraft)

: 956

Environmentally hazardous : yes

14 / 18

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 7.1 09/30/2023 42862-00021 Date of first issue: 01/06/2015

IMDG-Code

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S. (Vorinostat)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Vorinostat)

Class : 9 Packing group : III

Labels : CLASS 9 ERG Code : 171

Marine pollutant : yes(Vorinostat)

Remarks : Above applies only to containers over 119 gallons or 450

liters.

Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Combustible dust

Germ cell mutagenicity Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 7.1 09/30/2023 42862-00021 Date of first issue: 01/06/2015

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Vorinostat 149647-78-9
Cellulose 9004-34-6
Croscarmellose sodium 74811-65-7

California Permissible Exposure Limits for Chemical Contaminants

Cellulose 9004-34-6

The ingredients of this product are reported in the following inventories:

AICS : not determined


DSL : not determined

IECSC : not determined

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CAL PEL : California permissible exposure limits for chemical contami-

nants (Title 8, Article 107)

NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 7.1 09/30/2023 42862-00021 Date of first issue: 01/06/2015

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

ACGIH / TWA : 8-hour, time-weighted average CAL PEL / PEL : Permissible exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 09/30/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/04/2023

 7.1
 09/30/2023
 42862-00021
 Date of first issue: 01/06/2015

shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8